


# Data sheet

## 1005.9 RK 6-10 RD



Feed-through terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Red

### Business data

|                                            |                       |
|--------------------------------------------|-----------------------|
| Article number                             | 1005.9                |
| Article name                               | RK 6-10 RD            |
| GTIN (EAN)                                 | 4044211001346         |
| Packaging unit                             | 100                   |
| Quantity unit                              | PC                    |
| Weight per piece (not including packaging) | 14.8 g                |
| Weight per piece (including packaging)     | 15.45 g               |
| Unit of weight                             | G                     |
| Customs number                             | 85369010              |
| Country of origin                          | CZ                    |
| Prio-Article                               | 1005.2                |
| Product description                        | Feed-through terminal |

# Data sheet

## 1005.9 RK 6-10 RD

### Technical data

#### Dimensions

|                  |         |
|------------------|---------|
| Length           | 48 mm   |
| Width            | 8 mm    |
| Height TS 35/7.5 | 47 mm   |
| Height TS 32     | 51.5 mm |

#### Ratings

|                                                 |                    |
|-------------------------------------------------|--------------------|
| Rated voltage                                   | 800 V              |
| Rated current                                   | 57 A               |
| Rated cross-section                             | 10 mm <sup>2</sup> |
| Rated impulse voltage                           | 6 kV               |
| Overvoltage category                            | III                |
| Contamination degree                            | 3                  |
| Maximum power dissipation for nominal condition | 1.82 W             |

#### Connection data

|                                                          |                     |
|----------------------------------------------------------|---------------------|
| Connection principle                                     | Screw connection    |
| Connection position                                      | Lateral             |
| Connections                                              | 2                   |
| Number of terminals per level                            | 2                   |
| Number of levels                                         | 1                   |
| Wire cross-section single-core (rigid) / stranded, min.  | 0.2 mm <sup>2</sup> |
| Wire cross-section single core (rigid)/stranded, max.    | 10 mm <sup>2</sup>  |
| Wire cross-section stranded, min.                        | 0.2 mm <sup>2</sup> |
| Wire cross-section stranded, max.                        | 10 mm <sup>2</sup>  |
| Wire cross-section stranded with wire-end ferrules, min. | 0.2 mm <sup>2</sup> |
| Wire cross-section stranded with wire-end ferrules, max. | 10 mm <sup>2</sup>  |
| Wire cross-section AWG, min.                             | 22                  |
| Wire cross-section AWG, max.                             | 8                   |
| Stripping length                                         | 12 mm               |
| Screw head                                               | Slotted             |
| Screw threading                                          | M 4                 |
| Tightening torque, min.                                  | 1.2 Nm              |
| Tightening torque, max.                                  | 2 Nm                |

# Data sheet

## 1005.9 RK 6-10 RD



### Technical data

#### Materials

|                           |               |
|---------------------------|---------------|
| Insulation housing        | Polyamide 6.6 |
| Flammability class UL 94  | V-2           |
| Working temperature, min. | -40 °C        |
| Working temperature, max. | 105 °C        |

#### Further technical data

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| Mounting type                       | Mounting rail TS 35/7.5 and TS 32 |
| Gauge plug acc. to EN 60 947-1      | A5                                |
| Number of cross-connection channels | 1                                 |
| End plate required                  | ✓                                 |
| Number of test pick-off options     | 1                                 |

#### Environmental Product Compliance

|                                |            |
|--------------------------------|------------|
| REACH Conform                  | yes        |
| REACH Reference date           | 2023-06-14 |
| REACH Candidate Substance Note | No         |
| RoHS Conform                   | yes        |

# Data sheet

## 1005.9 RK 6-10 RD

### Approvals

#### Standards and regulations

|                      |                |
|----------------------|----------------|
| EAC approval         | TR ZU 004/2011 |
| EAC approval granted | yes            |

#### CSA approval

|                                  |              |
|----------------------------------|--------------|
| CSA approval                     | C22.2 No 158 |
| CSA approval granted             | yes          |
| CSA Usegroup C: rated voltage    | 600 V        |
| CSA Usegroup C: rated current    | 55 A         |
| CSA wire cross-section AWG, min. | 22           |
| CSA wire cross-section AWG, max. | 10           |
| CSA stripping length             | 12 mm        |
| CSA torque, max.                 | 2 Nm         |
| CSA torque, min.                 | 1.2 Nm       |
| CSA File Number                  | 042110_0_000 |

#### KEMA KEUR approval

|                                                   |                     |
|---------------------------------------------------|---------------------|
| KEMA KEUR approval                                | EN 60947-7-1:2009   |
| KEMA KEUR approval granted                        | yes                 |
| KEMA rated voltage                                | 800 V               |
| KEMA rated current                                | 57 A                |
| KEMA rated impulse voltage                        | 6 kV                |
| KEMA wire cross-section single core (rigid), min. | 0.2 mm <sup>2</sup> |
| KEMA wire cross-section single-core (rigid), max. | 10 mm <sup>2</sup>  |
| KEMA wire cross-section stranded, min.            | 0.2 mm <sup>2</sup> |
| KEMA wire cross-section stranded, max.            | 10 mm <sup>2</sup>  |
| KEMA torque, min.                                 | 1.2 Nm              |
| KEMA torque, max.                                 | 2 Nm                |

# Data sheet

## 1005.9 RK 6-10 RD



### Approvals



#### UL Recognized

|                                                     |          |
|-----------------------------------------------------|----------|
| UL approval                                         | UL 1059  |
| UL Usegroup C: rated voltage                        | 600 V    |
| UL Usegroup C: rated current                        | 65 A     |
| UL wire cross-section single-core (rigid) AWG, min. | 22       |
| UL wire cross-section single-core (rigid) AWG, max. | 6        |
| UL wire cross-section stranded AWG, min.            | 22       |
| UL wire cross-section stranded AWG, max.            | 6        |
| UL torque                                           | 12 Lb In |
| UL wire material                                    | Cu       |
| UL factory wiring                                   | 1        |
| UL field wiring                                     | 1        |
| UL File Number                                      | E95701   |
| UL Recognized                                       | 1        |

#### German Lloyd approval

|                            |                                           |
|----------------------------|-------------------------------------------|
| DNV GL Certificate number  | TAE000014T                                |
| DNV GL Location Classes    | Temperature: B, Humidity: B, Vibration: A |
| DNV GL approval granted    | 1                                         |
| DNV GL rated cross-section | 10 mm <sup>2</sup>                        |
| DNV GL rated current       | 61 A                                      |
| DNV GL rated voltage       | 750 V                                     |
| DNV GL test standard       | IEC 60947-7-1:2002                        |

Media



# Data sheet

## 1005.9 RK 6-10 RD

### Accessories

#### Cover



Cover, Length: 26.5 mm, Width: 8 mm, Colour: White

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2966.0</u>  | AD 1/8 WH    | 4044211056957 | 50 ST          |



Cover, Length: 32 mm, Width: 28 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2054.0</u>  | AD 4/32/B YE | 4044211048600 | 50 ST          |



Cover, Length: 32 mm, Width: 28 mm, Colour: Yellow

| Article number | Article name   | GTIN (EAN)    | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>2495.0</u>  | AD 4/32/B/E YE | 4044211052966 | 50 ST          |



Cover, Length: 26.5 mm, Width: 8 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2954.0</u>  | AD 1/8/B YE  | 4044211056827 | 50 ST          |

#### End plate




End plate, Width: 1.5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2001.2</u>  | AP 2,5-10 BG | 4044211047979 | 50             |

#### End stop

# Data sheet

## 1005.9 RK 6-10 RD



End stop, Mounting type: Mounting rail TS 35/7.5, Width: 9.5 mm, Colour: Beige

| Article number | Article name  | GTIN (EAN)    | Packaging unit |
|----------------|---------------|---------------|----------------|
| <u>2828.0</u>  | ES 35/K/ST BG | 4044211055547 | 50             |

### Insulated cross-connector



Insulated cross-connector, No. of poles: 10, Mounting type: Can be screwed on, Width: 78.4 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2753.2</u>  | QI 10 YE     | 4044211054892 | 10 ST          |



Insulated cross-connector, No. of poles: 4, Mounting type: Can be screwed on, Width: 28.8 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2752.2</u>  | QI 4 YE      | 4044211054885 | 20 ST          |



Insulated cross-connector, No. of poles: 2, Mounting type: Can be screwed on, Width: 13.6 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2750.2</u>  | QI 2 YE      | 4044211054861 | 50 ST          |




Insulated cross-connector, No. of poles: 3, Mounting type: Can be screwed on, Width: 21.7 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2751.2</u>  | QI 3 YE      | 4044211054878 | 50 ST          |

### Quick marking

# Data sheet

## 1005.9 RK 6-10 RD



Terminal marker / Pocket Maxicard, Length: 5 mm, Width: 8 mm, Colour: White

| Article number | Article name   | GTIN (EAN)    | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>9323.7</u>  | PMC SB 8/40 WH | 4044211129231 | 400 ST         |

### Insulation plate



Insulation plate, Colour: Beige

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2003.2</u>  | TRS 1 BG     | 4044211048068 | 100            |

### Screwdriver



Screwdriver with bare blade, Colour: Black-grey

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1087.0</u>  | SDB 0,8x4,0  | 4044211014803 | 1 ST           |

### ##INVERSE##CONTA-CONNECT



Test adapter, Length: 37.3 mm, Pitch size: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN)    | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2817.0</u>  | TA 8/1/ST    | 4044211055431 | 10 ST          |