



Crimping tool for crimping wire-end ferrules with and without plastic collars. Cross-section range: 0.5-6 mm<sup>2</sup> (AWG 2-10). Easy to use, Auto-lock for proper and complete crimping, Wires fed in from the front, Self-opening with built-in spring.

### Business data

Article number	<u>1100.0</u>
Article name	PZU 6
GTIN (EAN)	4044211016357
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	500 g
Weight per piece (including packaging)	576 g
Unit of weight	G
Customs number	82032000
Country of origin	DE
Product description	Crimping tool

---

### Technical data

---

#### Dimensions

Length	210 mm
--------	--------

#### Application

Crimp shape	Trapezoidal crimp
-------------	-------------------

Crimping range, min.	0.14 mm <sup>2</sup>
----------------------	----------------------

Crimping range, max.	6 mm <sup>2</sup>
----------------------	-------------------

Crimping range AWG, min.	26
--------------------------	----

Crimping range AWG, max.	10
--------------------------	----

Wire-end ferrule cross-section, min.	0.5 mm <sup>2</sup>
--------------------------------------	---------------------

Max wire-end ferrule cross-section	6 mm <sup>2</sup>
------------------------------------	-------------------

#### Environmental Product Compliance

REACH Conform	Yes
---------------	-----

REACH Reference date	2024-06-27
----------------------	------------

REACH Candidate Substance Note	No
--------------------------------	----

RoHS Conform	Yes
--------------	-----

---

**Media**

---

---

**Accessories**

---