# Data sheet

## 12340.1 PK-TS/23/5,08 GN



Plug-in connection system, Screw connection, No. of poles: 23, Width: 118.36 mm, Colour: Green

### Business data

| | |
|---|---|
| Article number | 12340.1 |
| Article name | PK-TS/23/5,08 GN |
| GTIN (EAN) | 4044211030094 |
| Connector version | Attached plug-in connector |
| Packaging unit | 25 |
| Quantity unit | PC |
| Packaging type | Carton |
| Type of banding | Without |
| Weight per piece (not including packaging) | 59 g |
| Weight per piece (including packaging) | 67 g |
| Unit of weight | G |
| Customs number | 85366930 |
| Country of origin | QU |
| Colour | Green |

# Data sheet

## 12340.1 PK-TS/23/5,08 GN

## Technical data

### Dimensions

| | |
|---|---|
| Length | 42.5 mm |
| Length of male pin block | 20.6 mm |
| Width | 118.36 mm |
| Width left | 3.3 mm |
| Width right | 3.3 mm |
| Height TS 35/7.5 | 35.5 mm |
| Height TS 32 | 40.5 mm |
| Pitch | 5.08 mm |

### Ratings

| | |
|---|---|
| Rated voltage | 250 V |
| Rated current | 10 A |
| Rated cross-section | 2.5 mm² |
| Rated impulse voltage | 4 kV |
| Overvoltage category | III |
| Contamination degree | 3 |

### Connection data

| | |
|---|---|
| Connection principle | Screw connection |
| Angle of wire connection/contact | 90° (vertically upwards) |
| No. of poles | 23 |
| Wire cross-section single-core (rigid) / stranded, min. | 0.2 mm² |
| Wire cross-section single core (rigid)/stranded, max. | 4 mm² |
| Wire cross-section stranded, min. | 0.2 mm² |
| Wire cross-section stranded, max. | 2.5 mm² |
| Wire cross-section stranded with wire-end ferrules, min. | 0.25 mm² |
| Wire cross-section stranded with wire-end ferrules, max. | 2.5 mm² |
| Wire cross-section AWG, min. | 28 |
| Wire cross-section AWG, max. | 12 |
| Stripping length | 6 mm |
| Screw threading | M 3 |
| Torque | 0.5 Nm |

# Data sheet

## 12340.1 PK-TS/23/5,08 GN

## Technical data

### Materials

| | |
|---|---|
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-0 |
| Working temperature, min. | -30 °C |
| Working temperature, max. | 105 °C |
| Clamping element | Brass |
| Contact flag | Copper alloy |
| Screws | Steel |

### Further technical data

| | |
|---|---|
| Storage temperature, min. | -40 °C |
| Storage temperature, max. | 105 °C |
| Insulation resistance | 1*10^13 Ohm x cm |
| Creepage-current resistance | CTI 600 |
| Glow wire flammability index GWFI | GWFI 850 |
| GWFI after-glow time | 30 Sek. |
| Glow wire ignition temperature GWIT | GWIT 775 °C |
| GWIT exposure time | 5 Sek. |
| Connection cycles, in compliance with standard | 5 |
| Plug-in cycles acc. to standard | 100 |

### Environmental Product Compliance

| | |
|---|---|
| REACH Conform | No |
| REACH Reference date | 2023-06-14 |
| REACH Candidate Substance Note | No |
| REACH CAS 1 Substance | LEAD |
| REACH CAS 1 Percent minimal | 0.1 % |
| REACH CAS 1 Percent maximum | 4 % |
| REACH CAS 1 Number | 7439-92-1 |
| RoHS Conform | yes |
| RoHS Exception rule | 6c |

## Approvals

### cUL Recognized

| | |
|---|---|
| cUL approval | C22.2 No 158 |
| cUL Usegroup B: rated voltage | 300 V |
| cUL Usegroup B: rated current | 15 A |
| cUL Usegroup C: rated voltage | 300 V |
| cUL Usegroup C: rated current | 15 A |
| cUL Usegroup D: rated voltage | 300 V |
| cUL Usegroup D: rated current | 15 A |
| cUL wire cross-section single-core (rigid) AWG, min. | 28 |
| cUL wire cross-section single-core (rigid) AWG, max. | 12 |
| cUL wire cross-section stranded AWG, min. | 28 |
| cUL wire cross-section stranded AWG, max. | 12 |
| cUL torque | 0.45 Nm |
| cUL wire material | Cu |
| cUL Recognized | 1 |

### UL Recognized

| | |
|---|---|
| UL approval | UL 1059 |
| UL Usegroup B: rated voltage | 300 V |
| UL Usegroup B: rated current | 15 A |
| UL Usegroup C: rated voltage | 300 V |
| UL Usegroup C: rated current | 15 A |
| UL Usegroup D: rated voltage | 300 V |
| UL Usegroup D: rated current | 15 A |
| UL wire cross-section single-core (rigid) AWG, min. | 28 |
| UL wire cross-section single-core (rigid) AWG, max. | 12 |
| UL wire cross-section stranded AWG, min. | 28 |
| UL wire cross-section stranded AWG, max. | 12 |
| UL torque | 4 Lb In |
| UL wire material | Cu |
| UL factory wiring | 1 |
| UL field wiring | 1 |
| UL Recognized | 1 |

## Approvals

### VDE approval

| | |
|---|---|
| VDE approval | DIN EN 61984 |
| VDE approval granted | yes |
| VDE rated voltage | 250 V |
| VDE rated current | 10 A |
| VDE rated current wire cross-section rigid, min. | 6 A |
| VDE rated current wire cross-section rigid, max. | 10 A |
| VDE rated current wire cross-section stranded, min. | 6 A |
| VDE rated current wire cross-section stranded, max. | 10 A |
| VDE rated impulse voltage | 4 kV |
| VDE wire cross-section rigid, min. | 0.5 mm² |
| VDE wire cross-section rigid, max. | 2.5 mm² |
| VDE wire cross-section stranded, min. | 0.5 mm² |
| VDE wire cross-section stranded, max. | 2.5 mm² |
| VDE overvoltage category | III |
| VDE contamination degree | 3 |

# Data sheet

## 12340.1 PK-TS/23/5,08 GN

### Media












## Accessories