

Data sheet

16103.2 GSM-USB-Cable



USB 2.0 connection cable [1 USB 2.0 plug A - 1 USB 2.0 plug Mini-B angled 90°] Cable length: 1.8 m, gold-plated plug contacts, colour: black

RAL: 9005

Business data

| | |
|--|-----------------|
| Article number | <u>16103.2</u> |
| Article name | GSM-USB-Cable |
| GTIN (EAN) | 4044211151584 |
| Packaging unit | 1 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 50 g |
| Weight per piece (including packaging) | 52 g |
| Unit of weight | G |
| Customs number | 85444290 |
| Country of origin | CN |
| Product description | Interface cable |
| Colour | Black |

16103.2 GSM-USB-Cable

Technical data

Connection data

| | |
|-------------------|----------|
| Plug-in connector | Mini USB |
|-------------------|----------|

Further technical data

| | |
|--------------|-------|
| Cable length | 1,8 m |
|--------------|-------|

| | |
|----------------|--------------|
| Connector type | Mini USB 90° |
|----------------|--------------|

Environmental Product Compliance

| | |
|---------------|-----|
| REACH Conform | yes |
|---------------|-----|

| | |
|----------------------|------------|
| REACH Reference date | 2024-01-23 |
|----------------------|------------|

| | |
|--------------------------------|----|
| REACH Candidate Substance Note | No |
|--------------------------------|----|

| | |
|--------------|-----|
| RoHS Conform | yes |
|--------------|-----|

Media

Data sheet

16103.2 GSM-USB-Cable

Accessories

##INVERSE##CONTA-ELECTRONICS



Compact reporting system for mobile networks, for monitoring analogue and digital values and remotely switching relay outputs. Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>16099.2</u> | GSM-PRO | 4044211151560 | 1 ST |
