

Data sheet

16177.2 WE-4AO



Webeasy I/O analogue output module, 4 analogue outputs 0 - 10 V, Mounting type: Mounting rail TS 35, Supply voltage range: 20 V - 28 VAC/DC

Business data

Article number	<u>16177.2</u>
Article name	WE-4AO
GTIN (EAN)	4044211207694
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	66 g
Weight per piece (including packaging)	106 g
Unit of weight	G
Customs number	85423190
Country of origin	NL
Product description	Controller module

Technical data

BUS data

Bus-Topologie / Kabellänge max.	multidrop line / 500m
Datenübertragungsrate / Bus-Teilnehmer max.	19k2 bps / 64
Bus protocol / interface	Modbus RTU / RS485, halb duplex, nicht isoliert

Dimensions

Length	95 mm
Width	36 mm
Height	60 mm

Connection data

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm ²
Wire cross-section single-core (rigid), max.	4 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	4 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm ²
Stripping length	6 mm
Torque	0.4 Nm


Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2024-01-23
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet

16177.2 WE-4AO

Media



24	003	0V	24	004	0V
INTERNAL BUS	A1		INTERNAL BUS	A1	⊖
INTERNAL BUS	A2		INTERNAL BUS	A2	⊖
INTERNAL BUS	A		INTERNAL BUS	A	⊖
INTERNAL BUS	B		INTERNAL BUS	B	⊖
24	001	0V	24	002	0V

Accessories
