

Interface-Relay-Compact (IRC) socket base IRC with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Business data				
Article number	<u>16191.2</u>			
Article name	IRC 110125V AC/DC			
GTIN (EAN)	4044211187279			
Packaging unit	10			
Quantity unit	PC			
Weight per piece (not including packaging)	27 g			
Weight per piece (including packaging)	27 g			
Unit of weight	G			
Customs number	85369010			
Country of origin	IT			
Product description	Relay socket base with screw connection			



Technical data

Dimensions		
Length	87 mm	
Width	6.2 mm	
Height TS 35 / 7.5 with BA	90.7 mm	
Ratings		
Rated voltage Un	110-125 VAC/DC -	
Overvoltage category	III	
Contamination degree	3	
Connection data		
Connection principle	Screw connection	
Wire cross-section single core (rigid), min.	0.2 mm ²	
Wire cross-section single-core (rigid), max.	2.5 mm ²	
Wire cross-section stranded, min.	0.2 mm ²	
Wire cross-section stranded, max.	2.5 mm ²	
Stripping length	10 mm	
Torque	0.5 Nm	
Output data		
Switching voltage / switching voltage max.	250 / 400 VAC	
Contact configuration	1 CO contact	
Materials		
Flammability class UL 94	V-2	
Working temperature, min.	-40 °C	
Working temperature, max.	70 °C	
Further technical data		
Degree of protection	IP20	
Status display	\checkmark	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2023-06-14	
REACH Candidate Substance Note	No	
RoHS Conform	yes	




Approvals

Standards and regulations			
CE compliant	yes		
cUL approval	CSA-C22.2 No. 14		
UL approval	UL 508		
UL Recognized	1		
cUL Recognized	1		



Media







Accessories

Cross-connector

 External cross- shortened, Volt	Compact (IRC), 16-pole,	can be	
Article number	Article name	GTIN (EAN)	Packaging unit
 16209.4	AQI/IRC/16 BK	4044211187651	10

Quick marking

Device and installation markers / Maxicard, Length: 6 mm, Width: 12 mm, Colour: White			
Article number	Article name	GTIN (EAN)	Packaging unit
3884.7	MC GS 6x12 R WH	4044211154547	600 ST
Device and installation markers / Maxicard, Length: 6 mm, Width: 12 mm, Colour: White			
Article number	Article name	GTIN (EAN)	Packaging unit
 3884.7	MC GS 6x12 R WH	4044211154547	600 ST
Device and inst	allation markers / Maxicard, Length: 6 m	m, Width: 12 mm, Colou	ur: White
Article number	Article name	GTIN (EAN)	Packaging unit
3885.7	MC GS 6x12 R So WH	4044211154554	600 ST

Adapter



Plug adapter for Interface-Relay-Compact (IRC), ribbon plug-in connector, 14-poles, according to IEC 60603-13, for 8 relay channels, Positive switching, Rated voltage: 24 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
16229.2	FCA/IRC	4044211187682	10 ST

15503.2



10 ST

Relays

	Plug-in miniature power relay, With power contact, 1 CO contact, Input voltage: 60 VDC			
34.51.7.024.0010 山田 ウ24V〒 6A 250V ~ 1	Article number	Article name	GTIN (EAN)	Packaging unit

PRC 1/60V DC



Plug-in miniature power relay, With multi-layer gold contact, 1 CO contact, Input voltage: 60 VDC

4044211118167

Article number Article name		GTIN (EAN)	Packaging unit
15568.2	PRC 1/60V DC Au	4044211118419	10 ST