

16381.2 GSM-ANTENNA-EXTERNAL- GSM+GPS-SMA-3M



Combined cellular/GPS antenna with omni-directional, SMA round connector (GSM/UMTS) and R-SMA round connector (GPS), connection cable length 3 m

RAL: 9005

Business data

Article number	<u>16381.2</u>
Article name	GSM-ANTENNA-EXTERNAL-GSM+GPS-SMA-3M
GTIN (EAN)	4044211207816
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	155 g
Weight per piece (including packaging)	158 g
Unit of weight	G
Customs number	85291069
Country of origin	EU
Product description	GSM-GPS antenna
Colour	Black

16381.2 GSM-ANTENNA-EXTERNAL- GSM+GPS-SMA-3M

Technical data

Dimensions

Length	81.3 mm
Width	81.3 mm
Height	29.6 mm
Installation height	14.6 mm
Drill hole diameter	13 mm

Connection data

Plug-in connector	SMA-Male
GPS frequency	1575,42 ± 1 MHz
Antennengewinn max.	1 dBi / 2 dBic
GSM frequency	800, 850, 900, 1900, 2100 MHz
Impedance	50 Ohm

Materials

Material	ABS
Working temperature, min.	-40 °C
Working temperature, max.	85 °C

Further technical data

Mounting type	External, screw
Cable length	3 m
Antenna shape	Puck

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2024-01-23
REACH Candidate Substance Note	No
RoHS Conform	yes

16381.2 GSM-ANTENNA-EXTERNAL- GSM+GPS-SMA-3M

Media

16381.2 GSM-ANTENNA-EXTERNAL- GSM+GPS-SMA-3M

Accessories

##INVERSE##CONTA-ELECTRONICS



Compact reporting system for mobile networks, for monitoring analogue and digital values and remotely switching relay outputs, incl. GSM positioning, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16369.2</u>	GSM-PRO2-GPS	4044211207748	1 ST



Compact reporting system for mobile networks to monitor analogue and digital values as well as remotely switch relay outputs, incl. GSM positioning, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16408.2</u>	GSM-PRO2E-GPS	4044211219024	1 ST