

16382.2 GSM-USB-MICRO-cable



USB 2.0 connection cable [1 USB 2.0 plug A - 1 USB 2.0 plug Micro-B] Cable length: 1.5 m, gold-plated plug contacts, colour: black

RAL: 9005

Business data

Article number	<u>16382.2</u>
Article name	GSM-USB-MICRO-cable
GTIN (EAN)	4044211207823
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	24 g
Weight per piece (including packaging)	27 g
Unit of weight	G
Customs number	85444290
Country of origin	CN
Product description	Interface cable
Colour	Black

16382.2 GSM-USB-MICRO-cable

Technical data

Connection data

Plug-in connector	Micro USB
-------------------	-----------

Further technical data

Cable length	1,5 m
--------------	-------

Connector type	Micro USB
----------------	-----------

Environmental Product Compliance

REACH Conform	Yes
---------------	-----

REACH Reference date	2024-06-27
----------------------	------------

REACH Candidate Substance Note	No
--------------------------------	----

RoHS Conform	Yes
--------------	-----

Media

16382.2 GSM-USB-MICRO-cable

Accessories

##INVERSE##CONTA-ELECTRONICS



Compact reporting system for mobile networks to monitor analogue and digital values, and to remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16368.2</u>	GSM-PRO2	4044211207731	1 ST



Compact reporting system for mobile networks, for monitoring analogue and digital values and remotely switching relay outputs, incl. GSM positioning, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16369.2</u>	GSM-PRO2-GPS	4044211207748	1 ST



Compact reporting system for mobile networks (up to and including 4G) to monitor analogue and digital values, and to remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16454.2</u>	GSM-PRO2-4G-EU	4044211222505	1 ST



Compact signaling system for mobile networks (up to and including 4G) to monitor analog and digital values as well as remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16455.2</u>	GSM-PRO2E-4G-EU	4044211222512	1 ST



Compact reporting system for mobile networks to monitor analogue and digital values as well as remotely switch relay outputs, incl. GSM positioning, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16408.2</u>	GSM-PRO2E-GPS	4044211219024	1 ST

16382.2 GSM-USB-MICRO-cable

##INVERSE##CONTA-ELECTRONICS



Compact signaling system for mobile networks (up to and including 4G) to monitor analog and digital values as well as remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16457.2</u>	GSM-PRO2E-4G-US	4044211222536	1 ST



Compact reporting system for mobile networks to monitor analogue and digital values as well as remotely switch relay outputs, incl. GSM positioning, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16408.2</u>	GSM-PRO2E-GPS	4044211219024	1 ST



Auto Send SMS Module, 10...30V dc, 24V ac. The module sends an SMS after power is connected. The telephone numbers are fully configurable using your Windows PC via a USB port. The GSM-TMM is therefore ideal as fault detector.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16489.2</u>	GSM-TMM-12VDC/24VUC	4044211236373	1 ST



Auto Send SMS Module, 230V AC. The module sends an SMS after power is connected. The telephone numbers are fully configurable using your Windows PC via a USB port. The GSM-TMM is therefore ideal as fault detector.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16511.2</u>	GSM-TMM-230VAC	4044211236366	1 ST



Auto Send SMS Module, 10...30V dc, 24V ac. The module sends an SMS after power is connected. The telephone numbers are fully configurable using your Windows PC via a USB port. The GSM-TMM is therefore ideal as fault detector.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16489.2</u>	GSM-TMM-12VDC/24VUC	4044211236373	1 ST