


17211.9

SQI 4/2 RD



Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 11.3 mm, Rated cross-section: 4 mm², Colour: Red

Business data

Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	1.3 g
Weight per piece (including packaging)	1.33 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	17211.8
Product description	Insulated cross-connector

17211.9

SQI 4/2 RD

Technical data

Dimensions

Length	4 mm
Width	11.3 mm
Height	23 mm
Pitch size	6 mm

Ratings

Voltage with partition, max.	1000 V
Voltage without partition, max.	1000 V
Rated current	32 A
Current load, max.	41 A
Rated cross-section	4 mm ²
Contamination degree	2

Connection data

No. of poles	2
--------------	---

Materials

Material	Bronze
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	2

Print

Colour	Red
--------	-----

Data sheet

17211.9

SQI 4/2 RD



Technical data

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2021-07-08
REACH Candidate Substance Note	No
RoHS Conform	yes

17211.9

SQI 4/2 RD

Accessories

Insulation cap for cross-connector



Insulating cap, Colour: Yellow

General order data

Product number:	Article name	GTIN (EAN)	Packaging unit
17200.8	SQIK 2,5-10 YE	4044211148539	20
