

Data sheet

2092.0 TS 15 GL



DIN rail, slotted, Width: 15 mm, Height: 5.5 mm, Material: Steel, Colour: natural

Business data

Article number	<u>2092.0</u>
Article name	TS 15 GL
GTIN (EAN)	4044211049003
Packaging unit	40
Quantity unit	M
Weight per piece (not including packaging)	150 g
Weight per piece (including packaging)	150 g
Unit of weight	G
Customs number	72166190
Country of origin	DE
Product description	DIN rail
Colour	Natural

Technical data

Dimensions

Length	2000 mm
Hole length	12 mm
Width	15 mm
Hole width	4.2
Height	5.5 mm
Hole spacing (mid-point to mid-point)	20 mm
Thickness	1 mm
Shape of hole	Slotted hole
Slotted hole	✓
Slotted	✓

Ratings

Max. short-circuit current	1.2 kA
Max. allowed thermal rated current with PEN function	The usage of protective earth steel busbars is not permitted for PEN functionality! A
Short-circuit resistance I _p	10 kA

Materials

Material	Steel
Surface	Galvanized, thick-film passivated

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2024-01-23
REACH Candidate Substance Note	No
RoHS Conform	yes

Approvals

Standards and regulations

Standards / specifications	DIN EN 60715
----------------------------	--------------



VDE approval

VDE approval	Acc. DIN VDE 0611-3
--------------	---------------------

Data sheet

2092.0 TS 15 GL

Media



Accessories
