



Fuse, Dimensions: 5x25 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 250 V, Rated current: 6.3 A

Business data

Article number	2099.0
Article name	SI K 5x25 6,300A-F
GTIN (EAN)	4044211049072
Indicator colour	Green
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	1.32 g
Weight per piece (including packaging)	1.4 g
Unit of weight	G
Customs number	85361010
Country of origin	EU
Product description	fuse

Technical data

Dimensions

Length	25 mm
Diameter of contact cap	5.2 mm
Optical defect display available	✓
Dimensions	5x25 mm

Ratings

Rated voltage	250 V
Rated current	6.3 A

Materials

Contact caps	Brass
Surface	Nickel
Tube	Ceramic

Further technical data

Trigger characteristic	Fast-acting (F)
Rated breaking capacity	1500 A @ AC 250 V
Voltage drop	170 mV
Power loss (@ 1.5 In)	2.5 W
Melting integral I ² ts	63 A ² s

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Media

Accessories
