



Wire-end ferrules, Max. wire cross-section: 6 mm<sup>2</sup>, Length: 26 mm, Length of copper pipe: 18 mm, Colour: Green

### Business data

|  |               |
|--|---------------|
| Article number                             | <u>2133.0</u> |
| Article name                               | H 6,0/26-T GN |
| GTIN (EAN)                                 | 4044211049522 |
| Packaging unit                             | 100           |
| Quantity unit                              | PC            |
| Weight per piece (not including packaging) | 0.61 g        |
| Weight per piece (including packaging)     | 0.63 g        |
| Unit of weight                             | G             |
| Customs number                             | 85369010      |
| Country of origin                          | DE            |
| Product description                        | Ferrules      |
| Colour                                     | Green         |

### Technical data

#### Dimensions

|                                  |        |
|----------------------------------|--------|
| Length                           | 26 mm  |
| Length of copper pipe            | 18 mm  |
| Diameter of copper pipe          | 3.5 mm |
| Diameter plastic collar          | 6.3 mm |
| Wall thickness of copper pipe    | 0.2 mm |
| Wall thickness of plastic collar | 0.3 mm |

#### Connection data

|                              |                   |
|------------------------------|-------------------|
| Wire cross-section, max.     | 6 mm <sup>2</sup> |
| Wire cross-section AWG, max. | 10                |
| Stripping length             | 20 mm             |

#### Materials

|                           |                                |
|---------------------------|--------------------------------|
| Copper pipe               | Copper alloy                   |
| Surface                   | Galvanically tin-plated, shiny |
| Plastic collar            | Polypropylene homopolymer      |
| Working temperature, min. | -5 °C                          |
| Working temperature, max. | 105 °C                         |

#### Further technical data

|                      |   |
|----------------------|---|
| Insulation available | ✓ |
|----------------------|---|

#### Environmental Product Compliance

|                                |            |
|--------------------------------|------------|
| REACH Conform                  | Yes        |
| REACH Reference date           | 2024-06-27 |
| REACH Candidate Substance Note | No         |
| RoHS Conform                   | Yes        |

---

### Approvals

---

### Standards and regulations

---

DIN 46228-4:1990

yes

---

---

### Media

---

---

### Accessories

---