

2389.0

H 10,0/15



Wire-end ferrules, Max. wire cross-section: 10 mm², Length: 15 mm, Colour: natural

Business data

| | |
|--|----------|
| Packaging unit | 500 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 0.38 g |
| Weight per piece (including packaging) | 0.39 g |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | DE |
| Product description | Ferrules |

2389.0

H 10,0/15

Technical data

Dimensions

| | |
|-------------------------------|--------|
| Length | 15 mm |
| Diameter of copper pipe | 4.5 mm |
| Diameter of feed-in funnel | 5.8 mm |
| Wall thickness of copper pipe | 0.2 mm |

Connection data

| | |
|------------------------------|--------------------|
| Wire cross-section, max. | 10 mm ² |
| Wire cross-section AWG, max. | 8 |
| Stripping length | 15 mm |

Materials

| | |
|---------------------------|--------------------------------|
| Copper pipe | Copper alloy |
| Surface | Galvanically tin-plated, shiny |
| Working temperature, max. | 120 °C |

Print

| | |
|--------|---------|
| Colour | Natural |
|--------|---------|

Environmental Product Compliance

| | |
|--------------------------------|------------|
| REACH Conform | yes |
| REACH Reference date | 2021-07-08 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

Data sheet



2389.0

H 10,0/15

Approvals

Standards and regulations

DIN 46228-1:1992

yes

2389.0

H 10,0/15

Accessories
