



Seal, Mounting type: Plug in, Length x width: 20.3 mm, Max. cable diameter: 10 mm, IP 66, Colour: Black

RAL: 9005

Business data

Article number	28529.4
Article name	KDS-DE 9-10 BK
GTIN (EAN)	4044211210953
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	5.3 g
Weight per piece (including packaging)	5.7 g
Unit of weight	G
Customs number	39259020
Country of origin	DE
Product description	Sealing Element
Colour	Black



Technical data

20.3 mm
20.3 mm
17.7 mm
TPE
НВ
-40 °C
120 °C
\checkmark
\checkmark
\checkmark
Plug in
IP66
\checkmark
9 mm
10 mm
1, 12, 4x (indoor use only)
1
yes
2023-06-14
No
yes



Approvals

Standards and regulations		
Standards / specifications Strain relief complying with DIN EN 62444		
cUL Recognized		
cUL approval	C22.2 No. 14-18	
cUL File Number	E489821	
cUL Recognized	1	
UL Recognized		
UL approval	UL 508A	
UL File Number	E489821	
UL Recognized	1	
UL Type Rating	1, 12, 4x (indoor use only)	
German Lloyd approval		
DNV GL Certificate number	TAE00003V7	
DNV GL Location Classes	Temperature: -40°C to 120°C, Humidity: B, Vibration: B, Ingress protection: IP66	
DNV GL approval granted	1	



Media





Accessories

Inlays

	Cable entry, Inlay, Mounting type: Plug in, IP 66, Colour: Black			
	Article number	Article name	GTIN (EAN)	Packaging unit
	28516.4	KDS-Inlay 1 BK	4044211210847	5 ST
	Cable entry, In	lay, Mounting type: Plug in, IP 66, Colou	r: Black	
	Article number	Article name	GTIN (EAN)	Packaging unit
	28517.4	KDS-Inlay 2 BK	4044211210854	5 ST
0	Cable entry, Inlay, Mounting type: Plug in, IP 66, Colour: Black			
	Article number	Article name	GTIN (EAN)	Packaging unit
Ŧ	28518.4	KDS-Inlay 4 BK	4044211210861	5 ST
	Cable entry, In	lay, Mounting type: Plug in, IP 66, Colou	r: Black	
	Article number	Article name	GTIN (EAN)	Packaging unit
• •	28519.4	KDS-Inlay 6 BK	4044211210014	5 ST

Screw frame

Cable entry with foamed-in seal, Mounting type: Screws, Length: 153 mm, Width: 70 mm, IP 66, Colour: Black

•	Article number	Article name	GTIN (EAN)	Packaging unit
	28504.4	KDS-SR 10/24 BK	4044211210809	1 ST

Cable entry with foamed-in seal, Mounting type: Screws, Length: 106 mm, Width: 70 mm, IP 66, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28500.4	KDS-SR 6/10 BK	4044211210021	1 ST



Screw frame

• •	Cable entry with foamed-in seal, Mounting type: Screws, Length: 126 mm, Width: 70 mm, IP 66, Colour: Black				
••	Article number	Article name	GTIN (EAN)	Packaging unit	
	28502.4	KDS-SR 8/16 BK	4044211210786	1 ST	
• •	Cable entry wi IP 66, Colour:	th foamed-in seal, Mounting type: Scre Black	ews, Length: 81 mm,	Width: 70 mm,	
	Article number	Article name	GTIN (EAN)	Packaging unit	
	28506.4	KDS-SR 1-4 BK	4044211210823	1 ST	

Locking frame

	Inner locking fra	ame, Length: 80 mm, Height: 11.5 mm, C	Colour: Black	
	Article number	Article name	GTIN (EAN)	Packaging unit
	28507.4	KDS-IVR 1-4 BK	4044211210830	10 ST

	Inner locking frame, Length: 105 mm, Height: 11.5 mm, Colour: Black			
	Article number	Article name	GTIN (EAN)	Packaging unit
	28501.4	KDS-IVR 6/10 BK	4044211210779	10 ST
	Inner locking fr	ame, Length: 125 mm, Height: 11.5 mm	, Colour: Black	
	Article number	Article name	GTIN (EAN)	Packaging unit
	28503.4	KDS-IVR 8/16 BK	4044211210793	10 ST
Inner locking frame, Length: 152 mm, Height: 11.5 mm, Colour: Black				
	Article number	Article name	GTIN (EAN)	Packaging unit
	28505.4	KDS-IVR 10/24 BK	4044211210816	10 ST

Actuating tool





Using the KDS BW1 actuating tool, the seals can be conveniently mounted in and dismantled from the frame. The ergonomic grip and the special shape enable simple and precise installations, especially for cabling applications in confined spaces., Material: Polyamide

Article number	Article name	GTIN (EAN)	Packaging unit
28622.0	KDS BW 1	4044211216597	1 ST