



Fuse, Dimensions: 5x20 mm, Trigger characteristic: Slow-acting (T); Rated voltage: 250 V, Rated current: 2.5 A

### Business data

Article number	2931.0
Article name	SI 5x20 2,500A-T
GTIN (EAN)	4044211056568
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	0.86 g
Weight per piece (including packaging)	0.9 g
Unit of weight	G
Customs number	85361010
Country of origin	DE
Product description	fuse

---

### Technical data

---

#### Dimensions

Length	20 mm
Diameter of contact cap	5.2 mm
Dimensions	5x20 mm

#### Ratings

Rated voltage	250 V
Rated current	2.5 A

#### Materials

Contact caps	Brass
Surface	Nickel
Tube	Glass

#### Further technical data

Trigger characteristic	Time-lag (T)
Rated breaking capacity	35 A @ AC 250 V
Voltage drop	80 mV
Power loss (@ 1.5 In)	0.6 W
Melting integral I <sup>2</sup> t <sub>s</sub>	26 A <sup>2</sup> s

#### Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2024-01-23
REACH Candidate Substance Note	No
RoHS Conform	yes

# Data sheet

**2931.0 SI 5x20 2,500A-T**



---

## Approvals

---

### Standards and regulations

---

Standards / specifications

IEC 60127-2/3 EN 60127-2/3 VDE 0820-2/3

---

# Data sheet

2931.0 SI 5x20 2,500A-T



---

Media

---

---

### Accessories

---