



Fuse, Dimensions: 5x20 mm, Trigger characteristic: Slow-acting (T); Rated voltage: 250 V, Rated current: 6.3 A

### Business data

Article number	2935.0
Article name	SI 5x20 6,300A-T
GTIN (EAN)	4044211056605
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	0.86 g
Weight per piece (including packaging)	0.9 g
Unit of weight	G
Customs number	85361010
Country of origin	DE
Product description	fuse

### Technical data

#### Dimensions

Length	20 mm
Diameter of contact cap	5.2 mm
Dimensions	5x20 mm

#### Ratings

Rated voltage	250 V
Rated current	6.3 A

#### Materials

Contact caps	Brass
Surface	Nickel
Tube	Glass

#### Further technical data

Trigger characteristic	Time-lag (T)
Rated breaking capacity	63 A @ AC 250 V
Voltage drop	70 mV
Power loss (@ 1.5 In)	1.3 W
Melting integral I <sup>2</sup> ts	230 A <sup>2</sup> s

#### Environmental Product Compliance

REACH Conform	Yes
REACH Reference date	2024-06-27
REACH Candidate Substance Note	No
RoHS Conform	Yes

# Data sheet

2935.0 SI 5x20 6,300A-T



---

## Approvals

---

### Standards and regulations

---

Standards / specifications

IEC 60127-2/3 EN 60127-2/3 VDE 0820-2/3

---

# Data sheet

2935.0 SI 5x20 6,300A-T



---

Media

---

---

### Accessories

---