

## 3196.2 STD-TS/LED(GN) GR



Switchgear cabinet socket with LED, Mounting type: TS 35/7.5, Width: 45 mm, Colour: Grey

**RAL:** 7032

### Business data

|  |                                    |
|--|------------------------------------|
| Article number                             | <u>3196.2</u>                      |
| Article name                               | STD-TS/LED(GN) GR                  |
| GTIN (EAN)                                 | 4044211141844                      |
| Packaging unit                             | 5                                  |
| Quantity unit                              | PC                                 |
| Weight per piece (not including packaging) | 69 g                               |
| Weight per piece (including packaging)     | 77.6 g                             |
| Unit of weight                             | G                                  |
| Customs number                             | 85369010                           |
| Country of origin                          | CN                                 |
| Product description                        | Switchgear cabinet socket with LED |
| Colour                                     | Grey                               |



## 3196.2 STD-TS/LED(GN) GR

### Technical data

#### Dimensions

|                  |       |
|------------------|-------|
| Length           | 75 mm |
| Width            | 45 mm |
| Height TS 35/7.5 | 67 mm |

#### Ratings

|               |          |
|---------------|----------|
| Rated voltage | 250 AC V |
| Rated current | 16 AC A  |

#### Connection data

|   |                     |
|---|---------------------|
| Wire cross-section single-core (rigid) / stranded, min. | 0.2 mm <sup>2</sup> |
| Wire cross-section single core (rigid)/stranded, max.   | 4 mm <sup>2</sup>   |
| Wire cross-section stranded, min.                       | 0.2 mm <sup>2</sup> |
| Wire cross-section stranded, max.                       | 2.5 mm <sup>2</sup> |
| Wire cross-section stranded with wire-end ferrules,min. | 0.2 mm <sup>2</sup> |
| Wire cross-section stranded with wire-end ferrules,max. | 2.5 mm <sup>2</sup> |
| Wire cross-section AWG, min.                            | 24                  |
| Wire cross-section AWG, max.                            | 12                  |
| Stripping length  | 8 mm                |
| Screw threading   | M 3                 |
| Tightening torque, min.                                 | 0.5 Nm              |
| Tightening torque, max.                                 | 1 Nm                |

#### Materials

|                           |               |
|---------------------------|---------------|
| Insulation housing        | Polyamide 6.6 |
| Flammability class UL 94  | V-0           |
| Working temperature, min. | -20 °C        |
| Working temperature, max. | 60 °C         |
| Material locking foot     | Metal         |

#### Further technical data

|                     |                                 |
|---------------------|---------------------------------|
| Illuminated display | LED, green with series resistor |
|---------------------|---------------------------------|

#### Environmental Product Compliance

|                                |            |
|--------------------------------|------------|
| REACH Conform                  | yes        |
| REACH Reference date           | 2024-01-23 |
| REACH Candidate Substance Note | No         |
| RoHS Conform                   | yes        |

## 3196.2 STD-TS/LED(GN) GR

---

### Approvals

---

#### Standards and regulations

---

Standards / specifications

Directive 2014/35/EU, DIN 49440-1:2006-01, DIN  
VDE 0620-1:2016-01

---

### Media

---

## 3196.2 STD-TS/LED(GN) GR

---

### Accessories

---

### Markers

---



Device and installation markers / Maxicard, Length: 17 mm, Width: 8 mm, Colour: White

| Article number | Article name      | GTIN (EAN)    | Packaging unit |
|----------------|-------------------|---------------|----------------|
| <u>3321.7</u>  | MC GS 8/17 R t WH | 4044211119058 | 200 ST         |

---