



External insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 16.1 mm, Rated current: 57 A; Colour: Yellow

RAL: 1026

Business data

Article number	3440.8
Article name	AQI 2/8/18 YE
GTIN (EAN)	4044211137540
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	2.6 g
Weight per piece (including packaging)	2.64 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Product description	External insulated cross-connector
Colour	Yellow



Technical data

Dimensions	
Width	16.1 mm
Pitch size	8 mm
Ratings	
Rated current	57 A
Contamination degree	3
Connection data	
No. of poles	2
Materials	
Material	Copper
Surface	Tin-plated
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C
Further technical data	
Mounting type	Plug in
Insulation available	\checkmark
Touch protection is available	\checkmark
Number of bridged terminals	2
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Media



ZCONTACLIP

Accessories

##INVERSE##CONTA-CONNECT



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1104.2	SIK 10/LED(RD)/20-30V DC/40-60V AC BG	4044211016753	25 ST



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number Article name		GTIN (EAN)	Packaging unit
1103.2	SIK 10/LED(RD)/12V DC/24V AC BG	4044211016548	25 ST



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number Article name		GTIN (EAN)	Packaging unit
<u>1105.2</u>	SIK 10/LED(RD)/40-60V DC/80-120V AC BG	4044211016906	25 ST



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1107.2	SIK 10/2 LED´s(RD)/24V DC BG	4044211016920	25 ST



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1106.2	SIK 10/LED(RD)/115V DC/230V AC BG	4044211016913	25



Fused terminal with disconnect plug, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17042.2	SIK 10/ST BG	4044211155797	25



##INVERSE##CONTA-CONNECT

	Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige			
	Article number	Article name	GTIN (EAN)	Packaging unit
	1101.2	SIK 10 BG	4044211016388	50
	Fused termina	l, Screw connection, Mounting type:N	Mounting rail TS 35/7.5	and TS 32,
11 11	Rated cross-section: 10 mm ² , Width: 8 mm, Colour: Black			
	Article number	Article name	GTIN (EAN)	Packaging unit
	17364.4	SIK 10 PA-G BK	4044211178406	50 ST
	Fused termina	with disconnect plug, Screw connect	ction, Mounting type:M	ounting rail TS
	35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige			
	Article number	Article name	GTIN (EAN)	Packaging unit
	17044.2	SIK 10/ST/5x20 BG	4044211155827	25 ST