

3455.4

FQI 1,5/5 BK



Insulated cross-connector, No. of poles: 5, Mounting type: Plug in, Width: 20.4 mm, Colour: Black

**RAL:** 9005

## Business data

Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	2.4 g
Weight per piece (including packaging)	2.5 g
Unit of weight	G
Customs number	85389099
Country of origin	CZ
Prio-Article	3455.8
Product description	Insulated cross-connector

3455.4

FQI 1,5/5 BK

---

## Technical data

---

### Dimensions

---

Length	4 mm
Width	20.4 mm
Pitch size	4.1 mm

---

### Ratings

---

Max. voltage	800 V
Rated current	17.5 A
Current load, max.	17,5 A
Rated cross-section	1.5 mm <sup>2</sup>

---

### Connection data

---

No. of poles	5
--------------	---

---

### Materials

---

Material	Copper
Surface	Tin-nickel
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

---

### Further technical data

---

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	5

---

### Print

---

Colour	Black
--------	-------

---

### Environmental Product Compliance

---

REACH Conform	yes
REACH Reference date	2021-07-08
REACH Candidate Substance Note	No
RoHS Conform	yes

---

3455.4

FQI 1,5/5 BK

---

## Accessories

---