

Data sheet

3723.9 ZQI 4/5 RD



Insulated cross-connector, No. of poles: 5, Mounting type: Plug in, Width: 28.4 mm, Rated cross-section: 4 mm², Colour: Red

Business data

| | |
|--|---------------------------|
| Article number | 3723.9 |
| Article name | ZQI 4/5 RD |
| GTIN (EAN) | 4044211111519 |
| Packaging unit | 20 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 3.6 g |
| Weight per piece (including packaging) | 3.62 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | CZ |
| Prio-Article | 3723.8 |
| Product description | Insulated cross-connector |

Data sheet

3723.9 ZQI 4/5 RD

Technical data

Dimensions

| | |
|------------|---------|
| Length | 4.5 mm |
| Width | 28.4 mm |
| Pitch size | 6 mm |

Ratings

| | |
|---------------------------------|-------------------|
| Voltage with partition, max. | 800 V |
| Voltage without partition, max. | 800 V |
| Rated current | 32 A |
| Rated cross-section | 4 mm ² |
| Contamination degree | 3 |

Connection data

| | |
|--------------|---|
| No. of poles | 5 |
|--------------|---|

Materials

| | |
|---------------------------|---------------|
| Material | Copper alloy |
| Surface | Tin-plated |
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-2 |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 105 °C |

Further technical data

| | |
|-------------------------------|---------|
| Mounting type | Plug in |
| Insulation available | ✓ |
| Touch protection is available | ✓ |
| Number of bridged terminals | 5 |

Environmental Product Compliance

| | |
|--------------------------------|----|
| REACH Candidate Substance Note | No |
|--------------------------------|----|

Media

Accessories

##INVERSE##CONTA-CONNECT

Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige



| Article number | Article name | GTIN (EAN) | Packaging unit |
|------------------------|--------------|---------------|----------------|
| 3515.2 | ZRK 4/2A BG | 4044211151751 | 100 |

Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige



| Article number | Article name | GTIN (EAN) | Packaging unit |
|------------------------|----------------|---------------|----------------|
| 1716.2 | ZRK 4/2A Ex BG | 4044211058579 | 100 |

Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige



| Article number | Article name | GTIN (EAN) | Packaging unit |
|------------------------|----------------|---------------|----------------|
| 1717.2 | ZRK 4/3A Ex BG | 4044211058609 | 100 |

Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige



| Article number | Article name | GTIN (EAN) | Packaging unit |
|------------------------|--------------|---------------|----------------|
| 3516.2 | ZRK 4/3A BG | 4044211151775 | 100 |

Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige



| Article number | Article name | GTIN (EAN) | Packaging unit |
|------------------------|----------------|---------------|----------------|
| 1718.2 | ZRK 4/4A Ex BG | 4044211058630 | 100 |

Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige



| Article number | Article name | GTIN (EAN) | Packaging unit |
|------------------------|--------------|---------------|----------------|
| 3517.2 | ZRK 4/4A BG | 4044211151782 | 100 |