



Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 58.9 mm, Rated cross-section: 4 mm<sup>2</sup>, Colour: Red

### Business data

|  |                           |
|--|---------------------------|
| Article number                             | 3728.9                    |
| Article name                               | ZQI 4/10 RD               |
| GTIN (EAN)                                 | 4044211111663             |
| Packaging unit                             | 10                        |
| Quantity unit                              | PC                        |
| Weight per piece (not including packaging) | 7.28 g                    |
| Weight per piece (including packaging)     | 7.48 g                    |
| Unit of weight                             | G                         |
| Customs number                             | 85389099                  |
| Country of origin                          | CZ                        |
| Prio-Article                               | 3728.8                    |
| Product description                        | Insulated cross-connector |

# Data sheet

## 3728.9 ZQI 4/10 RD

---

### Technical data

---

#### Dimensions

|            |         |
|------------|---------|
| Length     | 4.5 mm  |
| Width      | 58.9 mm |
| Pitch size | 6 mm    |

#### Ratings

|                                 |                   |
|---------------------------------|-------------------|
| Voltage with partition, max.    | 800 V             |
| Voltage without partition, max. | 800 V             |
| Rated current                   | 32 A              |
| Rated cross-section             | 4 mm <sup>2</sup> |
| Contamination degree            | 3                 |

#### Connection data

|              |    |
|--------------|----|
| No. of poles | 10 |
|--------------|----|

#### Materials

|                           |               |
|---------------------------|---------------|
| Material                  | Copper alloy  |
| Surface                   | Tin-plated    |
| Insulation housing        | Polyamide 6.6 |
| Flammability class UL 94  | V-2           |
| Working temperature, min. | -40 °C        |
| Working temperature, max. | 105 °C        |

#### Further technical data

|                               |         |
|-------------------------------|---------|
| Mounting type                 | Plug in |
| Insulation available          | ✓       |
| Touch protection is available | ✓       |
| Number of bridged terminals   | 10      |

#### Environmental Product Compliance

|                                |    |
|--------------------------------|----|
| REACH Candidate Substance Note | No |
|--------------------------------|----|

# Data sheet

3728.9 ZQI 4/10 RD



---

## Media

---

---

### Accessories

---

### ##INVERSE##CONTA-CONNECT

Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige



| Article number         | Article name | GTIN (EAN)    | Packaging unit |
|------------------------|--------------|---------------|----------------|
| <a href="#">3515.2</a> | ZRK 4/2A BG  | 4044211151751 | 100            |

Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige



| Article number         | Article name   | GTIN (EAN)    | Packaging unit |
|------------------------|----------------|---------------|----------------|
| <a href="#">1716.2</a> | ZRK 4/2A Ex BG | 4044211058579 | 100            |

Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige



| Article number         | Article name   | GTIN (EAN)    | Packaging unit |
|------------------------|----------------|---------------|----------------|
| <a href="#">1717.2</a> | ZRK 4/3A Ex BG | 4044211058609 | 100            |

Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige



| Article number         | Article name | GTIN (EAN)    | Packaging unit |
|------------------------|--------------|---------------|----------------|
| <a href="#">3516.2</a> | ZRK 4/3A BG  | 4044211151775 | 100            |

Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige



| Article number         | Article name   | GTIN (EAN)    | Packaging unit |
|------------------------|----------------|---------------|----------------|
| <a href="#">1718.2</a> | ZRK 4/4A Ex BG | 4044211058630 | 100            |

Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm<sup>2</sup>, Width: 6.1 mm, Colour: Beige



| Article number         | Article name | GTIN (EAN)    | Packaging unit |
|------------------------|--------------|---------------|----------------|
| <a href="#">3517.2</a> | ZRK 4/4A BG  | 4044211151782 | 100            |