

## 4950.0 SI 6,3x32 0,100A-T



Fuse, Dimensions: 6.3x32 mm, Trigger characteristic: Slow-acting (T); Rated voltage: 500 / 440 / 250 V, Rated current: 0.1 A

### Business data

Article number	<u>4950.0</u>
Article name	SI 6,3x32 0,100A-T
GTIN (EAN)	4044211109127
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	2.66 g
Weight per piece (including packaging)	2.7 g
Unit of weight	G
Customs number	85361010
Country of origin	EU
Product description	fuse

## 4950.0 SI 6,3x32 0,100A-T

---

### Technical data

---

#### Dimensions

Length	31.8 mm
Diameter of contact cap	6.35 mm
Dimensions	6,3x32 mm

#### Ratings

Rated voltage	500 / 440 / 250 V
Rated current	0.1 A

#### Materials

Contact caps	Brass
Surface	Nickel
Tube	Ceramic

#### Further technical data

Trigger characteristic	Time-lag (T)
Rated breaking capacity	1,5 kA @ AC 500 (cos $\phi$ = 1 10 kA @ AC 440 V cos $\phi$ = 0,3)
Voltage drop	3600 mV
Power loss (@ 1.5 In)	1.3 W
Melting integral I <sup>2</sup> ts	0.04 A <sup>2</sup> s

#### Environmental Product Compliance

REACH Conform	Yes
REACH Reference date	2024-06-27
REACH Candidate Substance Note	No
RoHS Conform	Yes

# Data sheet

4950.0 SI 6,3x32 0,100A-T



---

Media

---

---

### Accessories

---