


Data sheet

15299.2 SD-B 15CZ



Interface module for D-SUB, Tension-spring connection and female D-SUB plug-in connector, Mounting type: Mounting rail TS 35, No. of poles: 15

Business data

Article number	<u>15299.2</u>
Article name	SD-B 15CZ
GTIN (EAN)	4044211078744
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	46.6 g
Weight per piece (including packaging)	109.8 g
Unit of weight	G
Customs number	85369010
Country of origin	NL
Product description	Interface module

Data sheet

15299.2 SD-B 15CZ

Technical data

Dimensions

Length	47 mm
Width	51 mm
Height TS 35/7.5	38 mm

Ratings

Overvoltage category	III
Contamination degree	2

Connection data

Connection principle	Tension-spring connection
Number of connections	1
No. of poles	15
Wire cross-section single core (rigid), min.	0.08 mm ²
Wire cross-section single-core (rigid), max.	2.5 mm ²
Wire cross-section stranded, min.	0.14 mm ²
Wire cross-section stranded, max.	2.5 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.14 mm ²
Wire cross-section stranded with wire-end ferrules, max.	1.5 mm ²
Stripping length	6 mm

Input data

Max. operating voltage AC/DC	125 V
Current load per channel, max.	1,5 A

Materials

Working temperature, min.	-20 °C
Working temperature, max.	50 °C

Further technical data

Mounting type	TS 35
Connector type	D-sub female socket block
Test voltage	0.67 kV
Shielded	✓

Technical data

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2024-01-23
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet

15299.2 SD-B 15CZ



Approvals

Standards and regulations



Standards / specifications

DIN VDE 0110 / EN 50178

Data sheet

15299.2 SD-B 15CZ

Media



Accessories
