

Data sheet

15593.2 PRS 4/230V AC eco



Plug-in industrial relays with power contacts, 2 CO contacts, Test button, Status LED, Mechanical switching position indicator, Input voltage: 230 VAC

Business data

Article number	15593.2
Article name	PRS 4/230V AC eco
GTIN (EAN)	4044211118990
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	35.6 g
Weight per piece (including packaging)	37.54 g
Unit of weight	G
Customs number	85364900
Country of origin	PL
Product description	Relay, opened design

Technical data

Dimensions

Length	27.5 mm
Width	21.2 mm
Height	33 mm

Ratings

Overvoltage category	II
Contamination degree	2

Input data

Working voltage	184-253 VAC -
Drop-out voltage	<0,2 Un
Coil voltage	230 VAC -
Power consumption	1,6 W
Coil resistance	16100 Ohm

Output data

Switching voltage / switching voltage max.	250 / 250 VAC
Continuous current max. / Inrush current max.	6 / 12 A
Contact configuration	4 CO contacts
Switching capacity, max.	1500 VA
Electrical lifespan (AC1)	>1x10 ⁵ (@ 6 A)
Mechanical lifespan	20x10 ⁶
Contact load, min.	300 mW

Materials

Contact material	AgNi
Working temperature, min.	-40 °C
Working temperature, max.	55 °C

Data sheet

15593.2 PRS 4/230V AC eco



Technical data

Further technical data

Degree of protection	RTI
Status display	✓
Insulation voltage coil/contact	2,5 kV
Response/release time	10 / 8 ms
Insulation voltage contact/contact	2 kV
Mechanical indicator	✓
Test button	✓
Vibration resistance NO/NC	5 g
Shock resistance NO/NC	10/5 g
Pinning	2,8 (AMP) mm

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Approvals

Standards and regulations

CE compliant	yes
--------------	-----


Media

Data sheet

15593.2 PRS 4/230V AC eco

Accessories

##INVERSE##CONTA-ELECTRONICS



Relay socket base PRS, for industrial relay with 4 CO contacts, Screw connection, Plug-in option for input/suppression modules, Mounting type: Mounting rail TS 35

Article number	Article name	GTIN (EAN)	Packaging unit
<u>15137.2</u>	PRS 4	4044211046200	1 ST



Relay socket base PRS, for industrial relay with 4 CO contacts, Screw connection, Plug-in option for input/suppression modules, Mounting type: Mounting rail TS 35

Article number	Article name	GTIN (EAN)	Packaging unit
<u>15324.2</u>	PRS 4 G	4044211047139	1 ST



Pre-assembled relay module PRS..., Tension-spring connection, Consisting of: relay socket base and power contact relay, 4 CO contacts, Input voltage: 230 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>15627.2</u>	PRSU 4Z/230V AC eco	4044211121570	1 ST



Pre-assembled relay module PRS..., Screw connection, Consisting of: relay socket base and power contact relay, 4 CO contacts, Input voltage: 230 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>15621.2</u>	PRSU 4/230V AC eco	4044211121525	10 ST



Pre-assembled relay module PRS..., Screw connection, Consisting of: relay socket base and power contact relay, 4 CO contacts, Input voltage: 230 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>15624.2</u>	PRSU 4G/230V AC eco	4044211121549	1 ST



Pre-assembled relay module PRS..., Tension-spring connection, Consisting of: relay socket base and power contact relay, 4 CO contacts, Input voltage: 230 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>15627.2</u>	PRSU 4Z/230V AC eco	4044211121570	1 ST

Data sheet

15593.2 PRS 4/230V AC eco



##INVERSE##CONTA-ELECTRONICS



Relay socket base PRS, for industrial relay with 4 CO contacts, Push-in connection, Plug-in option for input/suppression modules and cross connections, Mounting type: Mounting rail TS 35

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16504.2</u>	PPRS 4	4044211236250	10 ST