

Data sheet

15627.2 PRSU 4Z/230V AC eco



Pre-assembled relay module PRS..., Tension-spring connection, Consisting of: relay socket base and power contact relay, 4 CO contacts, Input voltage: 230 VAC

Business data

Article number	15627.2
Article name	PRSU 4Z/230V AC eco
GTIN (EAN)	4044211121570
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	58 g
Weight per piece (including packaging)	71 g
Unit of weight	G
Customs number	85364900
Country of origin	DE
Product description	Complete module

Technical data

Dimensions

Length	98 mm
Width	31 mm
Height TS 35 / 7.5 with BA	69.2 mm

Ratings

Rated voltage Un	230 VAC -
Overvoltage category	III
Contamination degree	3

Connection data

Connection principle	Tension-spring connection
Wire cross-section single core (rigid), min.	0.2 mm ²
Wire cross-section single-core (rigid), max.	1.5 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	1.5 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
Wire cross-section stranded with wire-end ferrules, max.	1 mm ²
Stripping length	12 mm

Input data

Drop-out voltage	<0,2 Un
Operating range	184-253 VAC
Power consumption	1,6 W

Output data

Switching voltage / switching voltage max.	250 / 250 VAC
Continuous current max. / Inrush current max.	6 / 12 A
Contact configuration	4 CO contacts
Switching capacity, max.	1500 VA
Electrical lifespan (AC1)	>1x10 ⁵
Mechanical lifespan	20x10 ⁶
Contact load, min.	300 mW
Bounce time at close of the NO/NC contact	6/8 ms

Data sheet

15627.2 PRSU 4Z/230V AC eco



Technical data

Materials

Contact material	AgNi
Flammability class UL 94	V-0
Working temperature, min.	-25 °C
Working temperature, max.	70 °C

Further technical data

Degree of protection	IP20
Status display	✓
Insulation voltage coil/contact	2,5 kV
Response/release time	10 / 8 ms
Insulation voltage contact/contact	2 kV
Test button	✓
Vibration resistance NO/NC	5 g
Pinning	2.8 (fast-on) mm
Coil and contact connections are separated	✓

Environmental Product Compliance


REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Approvals

Standards and regulations

CE compliant	yes
--------------	-----

Media



Accessories

Screwdriver

Screwdriver with bare blade, Colour: Black-grey



Article number	Article name	GTIN (EAN)	Packaging unit
<u>1086.0</u>	SDB 0,6x3,5	4044211014797	1 ST

Relays



Plug-in industrial relays with power contacts, 2 CO contacts, Test button, Status LED, Mechanical switching position indicator, Input voltage: 230 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>15593.2</u>	PRS 4/230V AC eco	4044211118990	1 ST