



DC/DC converter module, regulated, Screw connection, Mounting type: Mounting rail TS 35, Input: 1-phase, Output: 24 VDC/0.5 A

### Business data

Article number	<u>15902.2</u>
Article name	CML-DCDC/24-0,5
GTIN (EAN)	4044211142094
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	55.7 g
Weight per piece (including packaging)	79.7 g
Unit of weight	G
Customs number	85423990
Country of origin	NL
Product description	Converter unit

### Technical data

#### Dimensions

Length	93.1 mm
Width	6.2 mm
Height TS 35/7.5	102.5 mm

#### Ratings

Overvoltage category	III
Contamination degree	2

#### Connection data

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm <sup>2</sup>
Wire cross-section single-core (rigid), max.	2.5 mm <sup>2</sup>
Wire cross-section stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded, max.	2.5 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm <sup>2</sup>
Stripping length	12 mm
Torque	0.6 Nm

#### Input data

Input voltage DC min.	32 V
Input voltage DC max.	65 V
Input current with max. load	350 mA
Zero-load current	<5 mA

#### Output data

Short-circuit current	0,7 A
Power, max.	12 W
Residual ripple	40 mV

#### Materials

Working temperature, min.	-20 °C
Working temperature, max.	50 °C

---

### Technical data

---

#### Further technical data

Status display green	✓
Efficiency	85 %
Switching frequency	530 kHz
Short-circuit resistant	✓

#### Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2024-01-23
REACH Candidate Substance Note	No
RoHS Conform	yes

### Approvals

---

#### Standards and regulations

---

Standards / specifications


DIN VDE 0110 / EN 50178

---

---

### Media

---



---

### Accessories

---