Data sheet

16008.2 CP V 40-S-N-PE

Protective plug for overvoltage arrester type 2 with gas discharge tube, 1-channel, Rated voltage: 230 VAC

Business data

Article number	16008.2
Article name	CP V 40-S-N-PE
GTIN (EAN)	4044211144555
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	29 g
Weight per piece (including packaging)	41 g
Unit of weight	G
Customs number	85354000
Country of origin	CN
Product description	Replacement plug-in module

Data sheet

16008.2 CP V 40-S-N-PE

Technical data

Dimensions

Installation dimensions acc. to DIN 43880	1 Te

Ratings

Rated voltage Un	230 / 400 -
Rated discharge surge current In (8/20) µs	80 kA
Rated frequency min.	50 Hz
Rated frequency max.	60 Hz
Short-circuit resistance Ip	25 kA

Connection data

Connection principle	Plug in

Materials

Working temperature, min.	-40 °C
Working temperature, max.	85 °C

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet

16008.2 CP V 40-S-N-PE

Approvals

Standards and regulations

DIN EN 61643-11 (Germany)	Arrester type 2
EN 61643-11 (Europe)	Low voltage SPD - Class II test
IEC 61643-1 (International)	Low voltage SPD - Class II test
UL1449 ed.2 (USA)	Low voltage TVSS

Media

Accessories