


Data sheet

16106.2 SD-S15CZ-HD



Interface module for D-SUB, Tension-spring connection and male D-SUB HD plug-in connector, Mounting type: Mounting rail TS 35, No. of poles: 15

Business data

Article number	16106.2
Article name	SD-S15CZ-HD
GTIN (EAN)	4044211153823
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	42 g
Weight per piece (including packaging)	73 g
Unit of weight	G
Customs number	85369010
Country of origin	NL
Product description	Interface module

Technical data

Dimensions

Length	87 mm
Width	49 mm
Height TS 35/7.5	38 mm

Ratings

Overvoltage category	III
Contamination degree	2

Connection data

Connection principle	Tension-spring connection
Number of connections	1
No. of poles	15
Wire cross-section single core (rigid), min.	0.08 mm ²
Wire cross-section single-core (rigid), max.	2.5 mm ²
Wire cross-section stranded, min.	0.14 mm ²
Wire cross-section stranded, max.	2.5 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.14 mm ²
Wire cross-section stranded with wire-end ferrules, max.	1.5 mm ²
Stripping length	6 mm

Input data

Max. operating voltage AC/DC	125 V
Current load per channel, max.	1,5 A

Materials

Working temperature, min.	-20 °C
Working temperature, max.	50 °C

Further technical data

Mounting type	TS 35
Connector type	D-Sub high-density male pin block
Test voltage	0.67 kV
Shielded	✓

Data sheet

16106.2 SD-S15CZ-HD



Technical data

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2024-01-23
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet

16106.2 SD-S15CZ-HD



Approvals

Standards and regulations

Standards / specifications	DIN VDE 0110 / EN 50178
----------------------------	-------------------------

Media

Accessories
