



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRC... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 6 VAC/DC

Business data

Baomoco data	
Article number	16260.2
Article name	FIRCU 1/6V AC/DC
GTIN (EAN)	4044211200398
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	32.8 g
Weight per piece (including packaging)	32.8 g
Unit of weight	G
Customs number	85364900
Country of origin	DE
Product description	Relay terminal





Technical data	
Dimensions	
Length	87 mm
Width	6.2 mm
Height TS 35 / 7.5 with BA	90.7 mm
Ratings	
Rated voltage Un	6 VAC/DC -
Overvoltage category	III
Contamination degree	3
Connection data	
Connection principle	Push-in connection
Wire cross-section single core (rigid), min.	0.2 mm²
Wire cross-section single-core (rigid), max.	2.5 mm²
Wire cross-section stranded, min.	0.2 mm²
Wire cross-section stranded, max.	2.5 mm ²
Stripping length	8 mm
Input data	
Holding current	0,6 Un -
Drop-out voltage	0.1 Un
Operating range	0,8-1,1 Un
Power consumption	0,2 W
Output data	
Switching voltage / switching voltage max.	230 / 400 VAC
Continuous current max. / Inrush current max.	6 / 10 A
Contact configuration	1 CO contact
Switching capacity, max.	1500 VA
Electrical lifespan (AC1)	60x10 ³
Mechanical lifespan	10x10 ⁶
Contact load, min.	500 mW
Bounce time at close of the NO/NC contact	3/8 ms
Materials	
Contact material	AgNi
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	70 °C





Technical data	
Further technical data	
Degree of protection	IP20
Status display	✓
Insulation voltage coil/contact	1 kV
Response/release time	12 / 5 ms
Insulation voltage contact/contact	4 kV
Vibration resistance NO/NC	10/5 g
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes




16260.2 FIRCU 1/6V AC/DC

Approvals			
Standards and regulations			
CE compliant	yes		
cUL approval	CSA-C22.2 No. 14		
UL approval	UL 508		
UL Recognized	1		
cUL Recognized	1		





Media





Data sheet 16260.2 FIRCU 1/6V AC/DC



Accessories

Cross-connector

External cross-connector insulated for Interface-Relay-Compact (IRC), 16-pole, can be shortened, Voltage: 250 V, Current: 6 A

Article number	Article name	GTIN (EAN)	Packaging unit
16209.4	AQI/IRC/16 BK	4044211187651	10

Quick marking



Device and installation markers / Maxicard, Length: 6 mm, Width: 12 mm, Colour: White

Article number	Article name	GTIN (EAN)	Packaging unit
3884.7	MC GS 6x12 R WH	4044211154547	600 ST



Device and installation markers / Maxicard, Length: 6 mm, Width: 12 mm, Colour: White

Article number	Article name	GTIN (EAN)	Packaging unit
3885.7	MC GS 6x12 R So WH	4044211154554	600 ST



Device and installation markers / Maxicard, Length: 6 mm, Width: 12 mm, Colour: White

Article number	Article name	GTIN (EAN)	Packaging unit
3885.7	MC GS 6x12 R So WH	4044211154554	600 ST

Screwdriver

Screwdriver with bare blade, Colour: Black-grey



Relays

Data sheet 16260.2 FIRCU 1/6V AC/DC





Plug-in miniature power relay, With power contact, 1 CO contact, Input voltage: 5 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>15500.2</u>	PRC 1/5V DC	4044211118174	10 ST

Adapter



Plug adapter for Interface-Relay-Compact (IRC), ribbon plug-in connector, 14-poles, according to IEC 60603-13, for 8 relay channels, Positive switching, Rated voltage: 24 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
16229.2	FCA/IRC	4044211187682	10 ST



Connection adapter for Interface-Relay-Compact (IRC) with Push-In connection, connection doubler to 2x1.5mm²

Article number	Article name	GTIN (EAN)	Packaging unit
16354.2	DCA/FIRC	4044211204655	10 ST

Partition plate



Partition plate for Interface-Relay-Compact (IRC) for separating relay blocks, variable width: 1.5 or 6.2 mm

Article number	Article name	GTIN (EAN)	Packaging unit
16228.2	TW/IRC	4044211187675	10 ST