



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRCO... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 12 VAC/DC

### **Business data**

Baomoco data	
Article number	<u>16281.2</u>
Article name	FIRCOU 1/12V AC/DC
GTIN (EAN)	4044211200602
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	33.5 g
Weight per piece (including packaging)	33.5 g
Unit of weight	G
Customs number	85364900
Country of origin	DE
Product description	Relay terminal





Technical data	
Dimensions	
Length	87 mm
Width	6.2 mm
Height TS 35 / 7.5 with BA	90.7 mm
Ratings	
Rated voltage Un	12 VAC/DC -
Overvoltage category	III
Contamination degree	3
Connection data	
Connection principle	Push-in connection
Wire cross-section single core (rigid), min.	0.2 mm <sup>2</sup>
Wire cross-section single-core (rigid), max.	2.5 mm²
Wire cross-section stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded, max.	2.5 mm <sup>2</sup>
Stripping length	8 mm
Input data	
Holding current	0,6 Un -
Drop-out voltage	0.1 Un
Operating range	0,8-1,1 Un
Power consumption	0,2 W
Output data	
Switching voltage / switching voltage max.	230 / 400 VAC
Continuous current max. / Inrush current max.	6 / 10 A
Contact configuration	1 NO contact
Switching capacity, max.	1500 VA
Electrical lifespan (AC1)	60x10 <sup>3</sup>
Mechanical lifespan	10x10 <sup>6</sup>
Contact load, min.	50 mW
Bounce time at close of the NO/NC contact	3/8 ms
Materials	
Contact material	AgNi
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	70 °C



## 16281.2 FIRCOU 1/12V AC/DC

Further technical data	
Degree of protection	IP20
Status display	✓
Insulation voltage coil/contact	1 kV
Response/release time	12 / 5 ms
Insulation voltage contact/contact	4 kV
Vibration resistance NO/NC	10/5 g
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes



## 16281.2 FIRCOU 1/12V AC/DC

Approvals		
Standards and regulations		
CE compliant	yes	
cUL approval	CSA-C22.2 No. 14	
UL approval	UL 508	
UL Recognized	1	
cUL Recognized	1	





Media







#### **Accessories**

#### **Cross-connector**

External cross-connector insulated for Interface-Relay-Compact (IRC), 16-pole, can be shortened, Voltage: 250 V, Current: 6 A

		Δ

Article number	Article name	GTIN (EAN)	Packaging unit
16209.4	AQI/IRC/16 BK	4044211187651	10

### **Quick marking**



Device and installation markers / Maxicard, Length: 6 mm, Width: 12 mm, Colour: White

Article number	Article name	GTIN (EAN)	Packaging unit
3884.7	MC GS 6x12 R WH	4044211154547	600 ST



Device and installation markers / Maxicard, Length: 6 mm, Width: 12 mm, Colour: White

Article number	Article name	GTIN (EAN)	Packaging unit
3884.7	MC GS 6x12 R WH	4044211154547	600 ST



Device and installation markers / Maxicard, Length: 6 mm, Width: 12 mm, Colour: White

Article number	Article name	GTIN (EAN)	Packaging unit
3885.7	MC GS 6x12 R So WH	4044211154554	600 ST

#### Screwdriver

Screwdriver with bare blade, Colour: Black-grey



Article number	Article name	GTIN (EAN)	Packaging unit
1086.0	SDB 0,6x3,5	4044211014797	1 ST

#### Relays







Plug-in miniature power relay, With power contact, 1 CO contact, Input voltage: 12 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>15501.2</u>	PRC 1/12V DC	4044211118136	10 ST

#### **Adapter**



Plug adapter for Interface-Relay-Compact (IRC), ribbon plug-in connector, 14-poles, according to IEC 60603-13, for 8 relay channels, Positive switching, Rated voltage: 24 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
16229.2	FCA/IRC	4044211187682	10 ST



Connection adapter for Interface-Relay-Compact (IRC) with Push-In connection, connection doubler to 2x1.5mm<sup>2</sup>

Article number	Article name	GTIN (EAN)	Packaging unit
16354.2	DCA/FIRC	4044211204655	10 ST

#### **Partition plate**



Partition plate for Interface-Relay-Compact (IRC) for separating relay blocks, variable width: 1.5 or 6.2 mm

Article number	Article name	GTIN (EAN)	Packaging unit
16228.2	TW/IRC	4044211187675	10 ST