



Signal converter for converting voltage/current signals to an analogue standard signal, Screw connection, Mounting type: Mounting rail TS 35, Supply voltage: 24 VDC

Business data

Article number	16374.2
Article name	CAE/I-I/020-010
GTIN (EAN)	4044211207502
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	49 g
Weight per piece (including packaging)	88 g
Unit of weight	G
Customs number	85423990
Country of origin	NL
Product description	Converter module

Technical data

Dimensions

Length	87 mm
Width	25 mm
Height	73 mm

Ratings

Overvoltage category	III
Contamination degree	2

Connection data

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm ²
Wire cross-section single-core (rigid), max.	4 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	2.5 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm ²
Stripping length	7 mm
Torque	0.6 Nm

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Media

Accessories

##INVERSE##CONTA-ELECTRONICS



Compact reporting system for mobile networks, for monitoring analogue and digital values and remotely switching relay outputs, incl. GSM positioning, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16369.2</u>	GSM-PRO2-GPS	4044211207748	1 ST



Compact signaling system for mobile networks to monitor analog and digital values as well as remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16407.2</u>	GSM-PRO2E	4044211219017	1 ST



Compact reporting system for mobile networks to monitor analogue and digital values as well as remotely switch relay outputs, incl. GSM positioning, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16408.2</u>	GSM-PRO2E-GPS	4044211219024	1 ST



Compact signaling system for mobile networks (up to and including 4G) to monitor analog and digital values as well as remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16455.2</u>	GSM-PRO2E-4G-EU	4044211222512	1 ST



Compact reporting system for mobile networks (up to and including 4G) to monitor analogue and digital values, and to remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16456.2</u>	GSM-PRO2-4G-US	4044211222529	1 ST

##INVERSE##CONTA-ELECTRONICS



Compact signaling system for mobile networks (up to and including 4G) to monitor analog and digital values as well as remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16457.2</u>	GSM-PRO2E-4G-US	4044211222536	1 ST



Compact reporting system for mobile networks to monitor analogue and digital values as well as remotely switch relay outputs, incl. GSM positioning, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16408.2</u>	GSM-PRO2E-GPS	4044211219024	1 ST