

Data sheet

16382.2 GSM-USB-MICRO-cable



USB 2.0 connection cable [1 USB 2.0 plug A - 1 USB 2.0 plug Micro-B] Cable length: 1.5 m, gold-plated plug contacts, colour: black

RAL: 9005

Business data

| | |
|--|---------------------|
| Article number | 16382.2 |
| Article name | GSM-USB-MICRO-cable |
| GTIN (EAN) | 4044211207823 |
| Packaging unit | 1 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 24 g |
| Weight per piece (including packaging) | 27 g |
| Unit of weight | G |
| Customs number | 85444290 |
| Country of origin | CN |
| Product description | Interface cable |
| Colour | Black |

Data sheet

16382.2 GSM-USB-MICRO-cable



Technical data

Connection data

| | |
|-------------------|-----------|
| Plug-in connector | Micro USB |
|-------------------|-----------|

Further technical data

| | |
|----------------|-----------|
| Cable length | 1,5 m |
| Connector type | Micro USB |

Environmental Product Compliance

| | |
|--------------------------------|------------|
| REACH Conform | yes |
| REACH Reference date | 2023-06-14 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

Media

16382.2 GSM-USB-MICRO-cable

Accessories

##INVERSE##CONTA-ELECTRONICS



Compact reporting system for mobile networks to monitor analogue and digital values, and to remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>16368.2</u> | GSM-PRO2 | 4044211207731 | 1 ST |



Compact reporting system for mobile networks, for monitoring analogue and digital values and remotely switching relay outputs, incl. GSM positioning, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>16369.2</u> | GSM-PRO2-GPS | 4044211207748 | 1 ST |



Compact reporting system for mobile networks (up to and including 4G) to monitor analogue and digital values, and to remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>16454.2</u> | GSM-PRO2-4G-EU | 4044211222505 | 1 ST |



Compact reporting system for mobile networks (up to and including 4G) to monitor analogue and digital values, and to remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>16454.2</u> | GSM-PRO2-4G-EU | 4044211222505 | 1 ST |



Compact reporting system for mobile networks to monitor analogue and digital values as well as remotely switch relay outputs, incl. GSM positioning, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------|---------------|----------------|
| <u>16408.2</u> | GSM-PRO2E-GPS | 4044211219024 | 1 ST |

16382.2 GSM-USB-MICRO-cable

##INVERSE##CONTA-ELECTRONICS



Compact signaling system for mobile networks (up to and including 4G) to monitor analog and digital values as well as remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-----------------|---------------|----------------|
| <u>16457.2</u> | GSM-PRO2E-4G-US | 4044211222536 | 1 ST |



Compact signaling system for mobile networks (up to and including 4G) to monitor analog and digital values as well as remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-----------------|---------------|----------------|
| <u>16457.2</u> | GSM-PRO2E-4G-US | 4044211222536 | 1 ST |



Compact reporting system for mobile networks to monitor analogue and digital values as well as remotely switch relay outputs, incl. GSM positioning, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------|---------------|----------------|
| <u>16408.2</u> | GSM-PRO2E-GPS | 4044211219024 | 1 ST |



Auto Send SMS Module, 230V AC. The module sends an SMS after power is connected. The telephone numbers are fully configurable using your Windows PC via a USB port. The GSM-TMM is therefore ideal as fault detector.

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>16511.2</u> | GSM-TMM-230VAC | 4044211236366 | 1 ST |



Auto Send SMS Module, 10...30V dc, 24V ac. The module sends an SMS after power is connected. The telephone numbers are fully configurable using your Windows PC via a USB port. The GSM-TMM is therefore ideal as fault detector.

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------------|---------------|----------------|
| <u>16489.2</u> | GSM-TMM-12VDC/24VUC | 4044211236373 | 1 ST |