

16451.2 GSM-ANTENNA-EXTERNAL-4G-3M



GSM UMTS LTE antenna with omni-directional characteristic, SMA round plug, Connecting cable length: 3 m

RAL: 9005

Business data

Article number	16451.2
Article name	GSM-ANTENNA-EXTERNAL-4G-3M
GTIN (EAN)	4044211222482
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	105 g
Weight per piece (including packaging)	107 g
Unit of weight	G
Customs number	85291069
Country of origin	CN
Product description	GSM antenna
Colour	Black

16451.2 GSM-ANTENNA-EXTERNAL-4G-3M

Technical data

Dimensions

Length	81.3 mm
Width	81.3 mm
Height	29.6 mm
Installation height	14.6 mm
Drill hole diameter	13 mm

Connection data

Plug-in connector	SMA-Male
Antennengewinn max.	2,5 dBi
GSM frequency	689 – 960, 1710 – 2690 MHz
Impedance	50 Ohm

Materials

Material	ABS
Working temperature, min.	-40 °C
Working temperature, max.	85 °C

Further technical data

Mounting type	External, screw
Cable length	3 m
Antenna shape	Puck

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Media

16451.2 GSM-ANTENNA-EXTERNAL-4G-3M

Accessories

Connection cables



Antenna cable to extend the connection cable of 4G antennas, Connections: SMA plug > SMA socket, Length: 10 m

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16494.2</u>	GSM-ANTENNA-EXTENSION-4G-10M	4044211236120	1 ST

##INVERSE##CONTA-ELECTRONICS



Compact reporting system for mobile networks (up to and including 4G) to monitor analogue and digital values, and to remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16454.2</u>	GSM-PRO2-4G-EU	4044211222505	1 ST



Compact signaling system for mobile networks (up to and including 4G) to monitor analog and digital values as well as remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16455.2</u>	GSM-PRO2E-4G-EU	4044211222512	1 ST



Compact reporting system for mobile networks (up to and including 4G) to monitor analogue and digital values, and to remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16456.2</u>	GSM-PRO2-4G-US	4044211222529	1 ST

16451.2 GSM-ANTENNA-EXTERNAL-4G-3M

##INVERSE##CONTA-ELECTRONICS



Compact signaling system for mobile networks (up to and including 4G) to monitor analog and digital values as well as remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16457.2</u>	GSM-PRO2E-4G-US	4044211222536	1 ST



Antenna cable to extend the connection cable of 4G antennas, Connections: SMA plug > SMA socket, Length: 10 m

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16494.2</u>	GSM-ANTENNA-EXTENSION-4G-10M	4044211236120	1 ST



Auto Send SMS Module, 230V AC. The module sends an SMS after power is connected. The telephone numbers are fully configurable using your Windows PC via a USB port. The GSM-TMM is therefore ideal as fault detector.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16511.2</u>	GSM-TMM-230VAC	4044211236366	1 ST



Auto Send SMS Module, 10...30V dc, 24V ac. The module sends an SMS after power is connected. The telephone numbers are fully configurable using your Windows PC via a USB port. The GSM-TMM is therefore ideal as fault detector.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16489.2</u>	GSM-TMM-12VDC/24VUC	4044211236373	1 ST