



Cross-connector, No. of poles: 3, Mounting type: Can be screwed on, Width: 54.8 mm, Rated cross-section: 70 mm<sup>2</sup>, Colour: natural

### Business data

Article number	<u>17266.0</u>
Article name	SQ 70/3
GTIN (EAN)	4044211186852
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	56.73 g
Weight per piece (including packaging)	57 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Product description	Cross-connector
Colour	Natural

### Technical data

#### Dimensions

Length	10 mm
Width	54.8 mm
Height	24.5 mm
Hole diameter	5.5 mm
Hole spacing (mid-point to mid-point)	20.5 mm
Pitch size	20.5 mm

#### Ratings

Max. voltage	1000 V
Rated current	192 A
Current load, max.	232 A
Rated cross-section	70 mm <sup>2</sup>
Contamination degree	3

#### Connection data

No. of poles	3
Screw head	Slotted
Screw threading	M 6
Tightening torque, min.	3.2 Nm
Tightening torque, max.	3.7 Nm

#### Materials

Material	Copper
Surface	Tin-plated
Surface screw	Galvanized

#### Further technical data

Mounting type	Screwable
Number of bridged terminals	3

#### Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2024-01-23
REACH Candidate Substance Note	No
RoHS Conform	yes

---

**Media**

---



### Accessories

#### ##INVERSE##CONTA-CONNECT



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 70 mm<sup>2</sup>, Width: 20.5 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>17161.2</u>	SRK 70/2A BG	4044211189273	10



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 70 mm<sup>2</sup>, Width: 20.5 mm, Colour: Black-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
<u>17162.2</u>	SRK 70/2A/PE BKYE	4044211186777	10 ST