

Insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 14.7 mm, Colour: Yellow

RAL: 1026

Business data

Article number	<u>17403.8</u>
Article name	FIQI 2,5-4/3 YE
GTIN (EAN)	4044211175962
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	1.7 g
Weight per piece (including packaging)	1.73 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Product description	Insulated cross-connector
Colour	Yellow

Technical data

Dimensions

Length	3.4 mm
Width	14.7 mm
Pitch size	5.1 mm

Ratings

Max. voltage	800 V
Rated current	24 A
Current load, max.	32 A
Rated cross-section	2.5 mm ²
Contamination degree	2

Connection data

No. of poles	3
--------------	---

Materials

Material	Bronze
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	3

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2024-01-23
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet


17403.8 FIQI 2,5-4/3 YE



Media

Accessories

##INVERSE##CONTA-CONNECT



Neutral-disconnect terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 5.1 mm, Colour: Blue

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3273.5</u>	FNT 2,5-4 BU	4044211138974	100 ST



Feed-through installation terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3276.2</u>	FRKI 2,5-4 BG	4044211139001	100