# Data sheet

## 17409.8 FIQI 2,5-4/9 YE



Insulated cross-connector, No. of poles: 9, Mounting type: Plug in, Width: 45.3 mm, Colour: Yellow

**RAL:** 1026

## Business data

| | |
|---|---|
| Article number | 17409.8 |
| Article name | FIQI 2,5-4/9 YE |
| GTIN (EAN) | 4044211176020 |
| Packaging unit | 10 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 5 g |
| Weight per piece (including packaging) | 5.1 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | DE |
| Product description | Insulated cross-connector |
| Colour | Yellow |

# Data sheet

## 17409.8 FIQI 2,5-4/9 YE

## Technical data

| | |
|---|---|
| **Dimensions** | |
| Length | 3.4 mm |
| Width | 45.3 mm |
| Pitch size | 5.1 mm |
| **Ratings** | |
| Max. voltage | 800 V |
| Rated current | 24 A |
| Current load, max. | 32 A |
| Rated cross-section | 2.5 mm² |
| Contamination degree | 2 |
| **Connection data** | |
| No. of poles | 9 |
| **Materials** | |
| Material | Bronze |
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-2 |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 105 °C |
| **Further technical data** | |
| Mounting type | Plug in |
| Insulation available | ✓ |
| Touch protection is available | ✓ |
| Number of bridged terminals | 9 |
| **Environmental Product Compliance** | |
| REACH Conform | yes |
| REACH Reference date | 2023-06-14 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

## Media

## Accessories

### ##INVERSE##CONTA-CONNECT



Neutral-disconnect terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 5.1 mm, Colour: Blue

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3273.5 | FNT 2,5-4 BU | 4044211138974 | 100 ST |



Feed-through installation terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 5.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3276.2 | FRKI 2,5-4 BG | 4044211139001 | 100 |