

# Data sheet

## 17503.4 KV/Mex-e 32 x 1,5 BK



Cable gland, Thread type: metric, Thread size: 32 mm, Material: Polyamide, Protection: IP68, Colour: Black

RAL: 9005

### Business data

|                                            |                      |
|--------------------------------------------|----------------------|
| Article number                             | 17503.4              |
| Article name                               | KV/Mex-e 32 x 1,5 BK |
| GTIN (EAN)                                 | 4044211133825        |
| Packaging unit                             | 25                   |
| Quantity unit                              | PC                   |
| Weight per piece (not including packaging) | 6.22 g               |
| Weight per piece (including packaging)     | 6.32 g               |
| Unit of weight                             | G                    |
| Customs number                             | 39269097             |
| Country of origin                          | EU                   |
| Prio-Article                               | 17503.4              |
| Product description                        | Cable gland          |

### Technical data

#### Dimensions

|                                   |       |
|-----------------------------------|-------|
| Width (enclosure size)            | 41 mm |
| Min. height (enclosure size) (TL) | 42 mm |
| Height (enclosure size) max. (TL) | 51 mm |
| Depth (enclosure size)            | 41 mm |

#### Thread

|                   |        |
|-------------------|--------|
| Thread type       | Metric |
| Thread size       | 32 mm  |
| Thread pitch      | 1.5 mm |
| Thread length (L) | 12 mm  |

#### Materials

|                           |           |
|---------------------------|-----------|
| Material                  | Polyamide |
| Flammability class UL 94  | V-0       |
| Working temperature, min. | -20 °C    |
| Working temperature, max. | 75 °C     |
| Type of seal              | Seal ring |
| Halogen-free              | ✓         |


#### Further technical data

|                             |        |
|-----------------------------|--------|
| Degree of protection        | IP68   |
| Spanner width (AF)          | 36 mm  |
| Strain relief               | ✓      |
| Cable diameter, min.        | 13 mm  |
| Cable diameter, max.        | 21 mm  |
| Impact resistant            | ✓      |
| Hexagonal corner size       | 40 mm  |
| Explosion protection        | ✓      |
| Installation torque cap nut | 3 Nm   |
| Installation torque fitting | 4.5 Nm |

#### Environmental Product Compliance

|                                |                        |
|--------------------------------|------------------------|
| REACH Conform                  | yes                    |
| REACH Reference date           | 2023-06-14, 2024-01-23 |
| REACH Candidate Substance Note | No                     |
| RoHS Conform                   | yes                    |

Media



---

**Accessories**

---