



Cable gland, Thread type: metric, Thread size: 50 mm, Material: Polyamide, Protection: IP68, Colour: Black

RAL: 9005

Business data

| | |
|--|----------------------|
| Article number | <u>17505.4</u> |
| Article name | KV/Mex-e 50 x 1,5 BK |
| GTIN (EAN) | 4044211133849 |
| Packaging unit | 4 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 6.22 g |
| Weight per piece (including packaging) | 6.32 g |
| Unit of weight | G |
| Customs number | 39269097 |
| Country of origin | EU |
| Prio-Article | 17505.4 |
| Product description | Cable gland |

Technical data

Dimensions

| | |
|-----------------------------------|-------|
| Width (enclosure size) | 61 mm |
| Min. height (enclosure size) (TL) | 59 mm |
| Height (enclosure size) max. (TL) | 72 mm |
| Depth (enclosure size) | 61 mm |

Thread

| | |
|-------------------|--------|
| Thread type | Metric |
| Thread size | 50 mm |
| Thread pitch | 1.5 mm |
| Thread length (L) | 14 mm |

Materials

| | |
|---------------------------|-----------|
| Material | Polyamide |
| Flammability class UL 94 | V-0 |
| Working temperature, min. | -20 °C |
| Working temperature, max. | 75 °C |
| Type of seal | Seal ring |
| Halogen-free | ✓ |


Further technical data

| | |
|-----------------------------|-------|
| Degree of protection | IP68 |
| Spanner width (AF) | 55 mm |
| Strain relief | ✓ |
| Cable diameter, min. | 23 mm |
| Cable diameter, max. | 35 mm |
| Impact resistant | ✓ |
| Hexagonal corner size | 61 mm |
| Explosion protection | ✓ |
| Installation torque cap nut | 12 Nm |
| Installation torque fitting | 13 Nm |

Environmental Product Compliance

| | |
|--------------------------------|------------------------|
| REACH Conform | yes |
| REACH Reference date | 2023-06-14, 2024-01-23 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

Media



Data sheet



17505.4 KV/Mex-e 50 x 1,5 BK

Accessories
