



Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

Business	data
-----------------	------

<u>17563.2</u>
SRKD 4/D2 BG
4044211234638
100
PC
19.16 g
20.11 g
G
85369010
BG
Double-level terminals with electronic components
Beige



Technical data

Dimensions	
Length	76 mm
Width	6.1 mm
Height TS 35/7.5	65 mm
Ratings	
Rated voltage	1000 V
Rated cross-section	4 mm ²
Rated impulse voltage	8 kV
Overvoltage category	III
Contamination degree	3
Connection data	
Connection principle	Screw connection
Connection position	Lateral
Connections	2 x 2
Number of terminals per level	2
Number of levels	2
Wire cross-section single-core (rigid) / stranded, min.	0.2 mm ²
Wire cross-section single core (rigid)/stranded, max.	6 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	6 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
Wire cross-section stranded with wire-end ferrules, max.	4 mm ²
Wire cross-section AWG, min.	26
Wire cross-section AWG, max.	10
Stripping length	10 mm
Screw head	Slotted
Screw threading	M 3
Tightening torque, min.	0.5 Nm
Tightening torque, max.	1 Nm



Technical data

Materials	
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C
Further technical data	
Mounting type	Mounting rail TS 35/7,5
Gauge plug acc. to EN 60 947-1	A4
Number of cross-connection channels	3
End plate required	\checkmark
Diode	1N4007 / 1000V / 1A
Number of test pick-off options	1
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes



Media





Accessories

End plate

	End plate, Widt	h: 1.5 mm, Colour: Beige		
•	Article number	Article name	GTIN (EAN)	Packaging unit
	17292.2	SAPD 2,5-4 BG	4044211190828	20

End stop

End stop, Moun Beige	ting type: Mounting rail TS 35/7.5 and TS	6 35/15, Width: 8 mm, C	olour:
Article number	Article name	GTIN (EAN)	Packaging unit
17250.2	SES 35 BG	4044211178253	50

Insulated cross-connector

Insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 17.4 mm, Rated cross-section: 4 mm², Colour: Yellow			
Article number	Article name	GTIN (EAN)	Packaging unit
17212.8	SQI 4/3 YE	4044211148652	50
	-connector, No. of poles: 2, Mounting typection: 4 mm², Colour: Yellow	pe: Plug in, Width: 11.3	mm,
Article number	Article name	GTIN (EAN)	Packaging unit
17211.8	SQI 4/2 YE	4044211148645	50

Insulated cross-connector, No. of poles: 8, Mounting type: Plug in, Width: 47.9 mm, Rated cross-section: 4 mm², Colour: Yellow

Article number	Article name	GTIN (EAN)	Packaging unit
17217.8	SQI 4/8 YE	4044211148706	10



Insulated cross-connector

	cross-section:			
111111111	Article number	Article name	GTIN (EAN)	Packaging unit
	17218.8	SQI 4/9 YE	4044211148713	10
		s-connector, No. of poles: 10, M ection: 4 mm², Colour: Yellow	lounting type: Plug in, Width	n: 60.1 mm,
	Article number	Article name	GTIN (EAN)	Packaging unit
	17219.8	SQI 4/10 YE	4044211148720	10
		s-connector, No. of poles: 5, Mo ection: 4 mm², Colour: Yellow	ounting type: Plug in, Width:	29.6 mm,
				Packaging
	Article number	Article name	GTIN (EAN)	unit
	Article number	SQI 4/5 YE	GTIN (EAN) 4044211148676	
	<u>17214.8</u> Insulated cross		4044211148676	unit 20
	<u>17214.8</u> Insulated cross	SQI 4/5 YE s-connector, No. of poles: 6, Mo	4044211148676	unit 20
	<u>17214.8</u> Insulated cross Rated cross-se	SQI 4/5 YE s-connector, No. of poles: 6, Mo ection: 4 mm², Colour: Yellow	4044211148676 punting type: Plug in, Width:	unit 20 35.7 mm, Packaging
	<u>17214.8</u> Insulated cross Rated cross-se Article number <u>17215.8</u> Insulated cross	SQI 4/5 YE s-connector, No. of poles: 6, Mo ection: 4 mm ² , Colour: Yellow Article name	4044211148676 Dunting type: Plug in, Width: GTIN (EAN) 4044211148683	unit 20 35.7 mm, Packaging unit 20
	<u>17214.8</u> Insulated cross Rated cross-se Article number <u>17215.8</u> Insulated cross	SQI 4/5 YE s-connector, No. of poles: 6, Mo ection: 4 mm², Colour: Yellow Article name SQI 4/6 YE s-connector, No. of poles: 4, Mo	4044211148676 Dunting type: Plug in, Width: GTIN (EAN) 4044211148683	unit 20 35.7 mm, Packaging unit 20
	<u>17214.8</u> Insulated cross Rated cross-se Article number <u>17215.8</u> Insulated cross Rated cross-se	SQI 4/5 YE s-connector, No. of poles: 6, Mo ection: 4 mm ² , Colour: Yellow Article name SQI 4/6 YE s-connector, No. of poles: 4, Mo ection: 4 mm ² , Colour: Yellow	4044211148676 Dounting type: Plug in, Width: GTIN (EAN) 4044211148683 Dounting type: Plug in, Width:	unit 20 35.7 mm, Packaging unit 20 23.5 mm, Packaging
	17214.8Insulated cross Rated cross-seArticle number17215.8Insulated cross Rated cross-seArticle number17213.8Insulated cross	SQI 4/5 YE s-connector, No. of poles: 6, Mo ection: 4 mm ² , Colour: Yellow Article name SQI 4/6 YE s-connector, No. of poles: 4, Mo ection: 4 mm ² , Colour: Yellow Article name	4044211148676 punting type: Plug in, Width: GTIN (EAN) 4044211148683 punting type: Plug in, Width: GTIN (EAN) 4044211148669	unit 20 35.7 mm, Packaging unit 20 23.5 mm, Packaging unit 20
	17214.8Insulated cross Rated cross-seArticle number17215.8Insulated cross Rated cross-seArticle number17213.8Insulated cross	SQI 4/5 YE s-connector, No. of poles: 6, Mo ection: 4 mm ² , Colour: Yellow Article name SQI 4/6 YE s-connector, No. of poles: 4, Mo ection: 4 mm ² , Colour: Yellow Article name SQI 4/4 YE s-connector, No. of poles: 30, M	4044211148676 punting type: Plug in, Width: GTIN (EAN) 4044211148683 punting type: Plug in, Width: GTIN (EAN) 4044211148669	unit 20 35.7 mm, Packaging unit 20 23.5 mm, Packaging unit 20



Insulated cross-connector

	Insulated cross-connector, No. of poles: 7, Mounting type: Plug in, Width: 41.8 mm, Rated cross-section: 4 mm², Colour: Yellow				
Article number	Article name	GTIN (EAN)	Packaging unit		
17216.8	SQI 4/7 YE	4044211148690	20		

Screwdriver

	Screwdriver with	h bare blade, Colour: Black-grey		
- COTTACLY T	Article number	Article name	GTIN (EAN)	Packaging unit
	<u>1086.0</u>	SDB 0,6x3,5	4044211014797	1 ST