



Cable gland, Thread type: metric, Thread size: 32 mm, Material: Polyamide, Protection: IP68 - 5 bar, Colour: Light grey

**RAL:** 7035

**Business data**

|                                            |                  |
|--------------------------------------------|------------------|
| Article number                             | 17603.2          |
| Article name                               | KV/M-L 32x1,5 GR |
| GTIN (EAN)                                 | 4044211157715    |
| Packaging unit                             | 25               |
| Quantity unit                              | PC               |
| Weight per piece (not including packaging) | 30.97 g          |
| Weight per piece (including packaging)     | 31.07 g          |
| Unit of weight                             | G                |
| Customs number                             | 39269097         |
| Country of origin                          | EU               |
| Prio-Article                               | 17603.2          |
| Product description                        | Cable gland      |

### Technical data

#### Dimensions

|                        |       |
|------------------------|-------|
| Width (enclosure size) | 40 mm |
|------------------------|-------|

|                        |       |
|------------------------|-------|
| Depth (enclosure size) | 40 mm |
|------------------------|-------|

#### Thread

|             |        |
|-------------|--------|
| Thread type | Metric |
|-------------|--------|

|             |       |
|-------------|-------|
| Thread size | 32 mm |
|-------------|-------|

|              |        |
|--------------|--------|
| Thread pitch | 1.5 mm |
|--------------|--------|

#### Materials

|          |           |
|----------|-----------|
| Material | Polyamide |
|----------|-----------|

|                          |     |
|--------------------------|-----|
| Flammability class UL 94 | V-0 |
|--------------------------|-----|

|                           |        |
|---------------------------|--------|
| Working temperature, min. | -40 °C |
|---------------------------|--------|

|                           |        |
|---------------------------|--------|
| Working temperature, max. | 100 °C |
|---------------------------|--------|

|                  |      |
|------------------|------|
| Sealing material | EPDM |
|------------------|------|

|              |   |
|--------------|---|
| Halogen-free | ✓ |
|--------------|---|

#### Further technical data

|                      |              |
|----------------------|--------------|
| Degree of protection | IP68 - 5 bar |
|----------------------|--------------|

|                    |       |
|--------------------|-------|
| Spanner width (AF) | 36 mm |
|--------------------|-------|

|                      |       |
|----------------------|-------|
| Cable diameter, min. | 13 mm |
|----------------------|-------|

|                      |       |
|----------------------|-------|
| Cable diameter, max. | 21 mm |
|----------------------|-------|

|                  |   |
|------------------|---|
| Impact resistant | ✓ |
|------------------|---|

|                       |       |
|-----------------------|-------|
| Hexagonal corner size | 40 mm |
|-----------------------|-------|

|                 |   |
|-----------------|---|
| Impact category | 4 |
|-----------------|---|

|                             |      |
|-----------------------------|------|
| Installation torque cap nut | 4 Nm |
|-----------------------------|------|

|                             |       |
|-----------------------------|-------|
| Installation torque fitting | 15 Nm |
|-----------------------------|-------|

|                         |   |
|-------------------------|---|
| Type of cable anchorage | A |
|-------------------------|---|

#### Environmental Product Compliance


|               |     |
|---------------|-----|
| REACH Conform | yes |
|---------------|-----|

|                      |                        |
|----------------------|------------------------|
| REACH Reference date | 2023-06-14, 2024-01-23 |
|----------------------|------------------------|

|                                |    |
|--------------------------------|----|
| REACH Candidate Substance Note | No |
|--------------------------------|----|

|              |     |
|--------------|-----|
| RoHS Conform | yes |
|--------------|-----|

Media



---

Accessories

---