

External insulated cross-connector, No. of poles: 4, Mounting type: Plug in, Width: 32.3 mm, Rated current: 27 A; Colour: Yellow

RAL: 1026

Business data

| | |
|--|------------------------------------|
| Article number | <u>2069.0</u> |
| Article name | AQI 4/8/11 YE |
| GTIN (EAN) | 4044211048754 |
| Packaging unit | 50 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 1.78 g |
| Weight per piece (including packaging) | 1.79 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | DE |
| Product description | External insulated cross-connector |
| Colour | Yellow |

Technical data

Dimensions

| | |
|-------|---------|
| Width | 32.3 mm |
|-------|---------|

| | |
|------------|------|
| Pitch size | 8 mm |
|------------|------|

Ratings

| | |
|---------------|------|
| Rated current | 27 A |
|---------------|------|

| | |
|----------------------|---|
| Contamination degree | 3 |
|----------------------|---|

Connection data

| | |
|--------------|---|
| No. of poles | 4 |
|--------------|---|

Materials

| | |
|----------|--------|
| Material | Copper |
|----------|--------|

| | |
|---------|------------|
| Surface | Tin-plated |
|---------|------------|

| | |
|--------------------|---------------|
| Insulation housing | Polyamide 6.6 |
|--------------------|---------------|

| | |
|--------------------------|-----|
| Flammability class UL 94 | V-2 |
|--------------------------|-----|

| | |
|---------------------------|--------|
| Working temperature, min. | -40 °C |
|---------------------------|--------|

| | |
|---------------------------|--------|
| Working temperature, max. | 105 °C |
|---------------------------|--------|

Further technical data

| | |
|---------------|---------|
| Mounting type | Plug in |
|---------------|---------|

| | |
|----------------------|---|
| Insulation available | ✓ |
|----------------------|---|

| | |
|-------------------------------|---|
| Touch protection is available | ✓ |
|-------------------------------|---|

| | |
|-----------------------------|---|
| Number of bridged terminals | 4 |
|-----------------------------|---|

Environmental Product Compliance

| | |
|---------------|-----|
| REACH Conform | yes |
|---------------|-----|

| | |
|----------------------|------------|
| REACH Reference date | 2024-01-23 |
|----------------------|------------|


| | |
|--------------------------------|----|
| REACH Candidate Substance Note | No |
|--------------------------------|----|

| | |
|--------------|-----|
| RoHS Conform | yes |
|--------------|-----|

Media


Accessories

##INVERSE##CONTA-CONNECT




Feed-through terminal for direct mount/block variant, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|------------------------|------------------|---------------|----------------|
| 1386.2 | KBL 6-10/10-D BG | 4044211044275 | 10 |




Feed-through terminal/block variant, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|------------------------|--------------|---------------|----------------|
| 1006.2 | KBL 6-10 BG | 4044211001414 | 10 ST |



Feed-through terminal for direct mount/block variant, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|------------------------|---------------|---------------|----------------|
| 1389.2 | KBL 6-10-D BG | 4044211044305 | 100 |



Feed-through terminal/block variant, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|------------------------|------------------|---------------|----------------|
| 1007.2 | KBL 6-10 m.B. BG | 4044211001629 | 10 ST |



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|------------------------|--------------|---------------|----------------|
| 1508.2 | BKA 10/10 BG | 4044211046002 | 10 ST |



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|------------------------|--------------|---------------|----------------|
| 1502.2 | BKA 10/4 BG | 4044211045715 | 20 ST |

##INVERSE##CONTA-CONNECT



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1500.2</u> | BKA 10/2 BG | 4044211045494 | 50 ST |



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1505.2</u> | BKA 10/7 BG | 4044211045951 | 20 ST |



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1504.2</u> | BKA 10/6 BG | 4044211045913 | 20 ST |



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1510.2</u> | BKA 10/12 BG | 4044211046101 | 10 ST |



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Width: 6 mm, Colour: Black-yellow


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-----------------|---------------|----------------|
| <u>1561.2</u> | BKA 4/1/PE BKYE | 4044211047320 | 100 ST |



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1507.2</u> | BKA 10/9 BG | 4044211045982 | 10 ST |

##INVERSE##CONTA-CONNECT



Ex feed-through terminal for direct mount ATEX-certified, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>1407.2</u> | BKA 10/1 Ex BG | 4044211044541 | 100 |



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1509.2</u> | BKA 10/11 BG | 4044211046071 | 10 ST |



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1501.2</u> | BKA 10/3 BG | 4044211045609 | 20 ST |



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1503.2</u> | BKA 10/5 BG | 4044211045821 | 20 ST |



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1506.2</u> | BKA 10/8 BG | 4044211045968 | 10 ST |



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1497.2</u> | BKA 10/1 BG | 4044211045319 | 50 |

##INVERSE##CONTA-CONNECT




Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Black-yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------|---------------|----------------|
| <u>1560.2</u> | BKA 2,5/1/PE BKYE | 4044211047313 | 100 ST |




Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------|---------------|----------------|
| <u>2451.2</u> | STK 1/LED(RD)/60V DC BG | 4044211052416 | 100 ST |




Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------------------|---------------|----------------|
| <u>2457.2</u> | STK 1/LED(RD)/115V AC BG | 4044211052478 | 100 ST |




Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1078.2</u> | STK 2 BG | 4044211013745 | 100 |



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1079.2</u> | STKD 1 BG | 4044211013905 | 50 |



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2190.2</u> | STK 1 BG | 4044211050115 | 100 |

##INVERSE##CONTA-CONNECT




Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1190.2</u> | STK 2/15 BG | 4044211026585 | 100 |




Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------------------|---------------|----------------|
| <u>2452.2</u> | STK 1/LED(RD)/115V DC BG | 4044211052423 | 100 ST |




Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------|---------------|----------------|
| <u>2454.2</u> | STK 1/LED(RD)/24V AC BG | 4044211052447 | 100 ST |




Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------|---------------|----------------|
| <u>2455.2</u> | STK 1/LED(RD)/48V AC BG | 4044211052454 | 100 ST |



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------|---------------|----------------|
| <u>2449.2</u> | STK 1/LED(RD)/24V DC BG | 4044211052393 | 100 ST |



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------------------|---------------|----------------|
| <u>2453.2</u> | STK 1/LED(RD)/230V DC BG | 4044211052430 | 100 ST |

##INVERSE##CONTA-CONNECT




Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------------------|---------------|----------------|
| <u>2458.2</u> | STK 1/LED(RD)/230V AC BG | 4044211052485 | 100 ST |




Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------|---------------|----------------|
| <u>2456.2</u> | STK 1/LED(RD)/60V AC BG | 4044211052461 | 100 ST |




Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2191.2</u> | STK 1/15 BG | 4044211050160 | 100 |




Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------|---------------|----------------|
| <u>2450.2</u> | STK 1/LED(RD)/48V DC BG | 4044211052409 | 100 ST |



Disconnect terminal, Screw connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2194.2</u> | TK 2/15/K BG | 4044211050214 | 100 |



Disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1381.2</u> | STK 2/K BG | 4044211044213 | 100 |

##INVERSE##CONTA-CONNECT




Disconnect terminal, Screw connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 4 mm², Width: 8 mm, Colour: Blue

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------|---------------|----------------|
| <u>1382.5</u> | STK 2/15/K BU | 4044211126278 | 100 |



Disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1383.2</u> | STKD 1/K BG | 4044211044244 | 50 |



Disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 8 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2193.2</u> | TK 2/K BG | 4044211050191 | 100 |