Data sheet

2096.0 SI K 5x25 1,000A-F

Fuse, Dimensions: 5x25 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 250 V, Rated current: 1 A

Business data

Article number	2096.0
Article name	SI K 5x25 1,000A-F
GTIN (EAN)	4044211049041
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	1.32 g
Weight per piece (including packaging)	1.4 g
Unit of weight	G
Customs number	85361010
Country of origin	EU
Product description	fuse

Data sheet

2096.0 SI K 5x25 1,000A-F

Technical data

Dimensions	
Length	25 mm
Diameter of contact cap	5.2 mm
Optical defect display available	✓
Dimensions	5x25 mm
Ratings	
Rated voltage	250 V
Rated current	1 A
Materials	
Contact caps	Brass
Surface	Nickel
Tube	Ceramic
Further technical data	
Trigger characteristic	Fast-acting (F)
Rated breaking capacity	1500 A @ AC 250 V
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet

2096.0 SI K 5x25 1,000A-F

Media

Data sheet

2096.0 SI K 5x25 1,000A-F

Accessories