# Data sheet 2368.0 QS 4





Cross-connection rail, No. of poles: 4, Mounting type: Can be screwed on, Width: 43.9 mm, Colour: natural

#### **Business data**

Article number	2368.0
Article name	QS 4
GTIN (EAN)	4044211051563
Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	3.4 g
Weight per piece (including packaging)	3.41 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Product description	Cross-connection rail
Colour	Natural

## **Data sheet**





Technical data		
Dimensions		
Length	6 mm	
Width	43.9 mm	
Height	2 mm	
Hole diameter	3.4 mm	
Hole spacing (mid-point to mid-point)	11.9 mm	
Pitch size	12 mm	
Connection data		
No. of poles	4	
Materials		
Material	Brass	
Surface	Nickel	
Further technical data		
Mounting type	Screwable	
Number of bridged terminals	4	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2023-06-14	
REACH Candidate Substance Note	No	
RoHS Conform	yes	

## **Data sheet**

2368.0 QS 4



Media



#### **Accessories**

#### ##INVERSE##CONTA-CONNECT



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
1004.4	SK 1/35 24V AC LED(RD) PA-G BK	4044211129989	20 ST



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
1119.4	SK 1/35 48V AC LED(RD) PA-G BK	4044211130008	20 ST



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1380.4</u>	SK 1/35 24V DC LED(RD) PA-G BK	4044211129972	20 ST



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
1380.4	SK 1/35 24V DC LED(RD) PA-G BK	4044211129972	20 ST



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
1367.4	SK 1/35 PA-G BK	4044211128555	20 ST

## **Data sheet**

### 2368.0 QS 4



#### ##INVERSE##CONTA-CONNECT



Fused terminal with screw cap for indicator fuses 5x25 mm, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour:Black

Article number	Article name	GTIN (EAN)	Packaging unit
1368.4	SK 1/35 m.K. PA-G BK	4044211129811	20 ST



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
1376.4	SK 1/35 115V AC G PA-G BK	4044211129958	20 ST



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
1376.4	SK 1/35 115V AC G PA-G BK	4044211129958	20 ST