



Cross-connector, No. of poles: 20, Mounting type: Can be screwed on, Width: 100.9 mm, Rated cross-section: 2.5 mm², Colour: natural

Business data

Article number	<u>2700.0</u>
Article name	Q 20
GTIN (EAN)	4044211054410
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	16.35 g
Weight per piece (including packaging)	16.42 g
Unit of weight	G
Customs number	85389099
Country of origin	CZ
Product description	Cross-connector
Colour	Natural

Technical data

Dimensions

Length	4 mm
Width	100.9 mm
Hole height	2.5 mm
Hole diameter	2.8 mm
Hole spacing (mid-point to mid-point)	5.1 mm
Pitch size	5 mm
Slotted hole	✓

Ratings

Voltage with partition, max.	400 V
Voltage without partition, max.	400 V
Rated current	20 A
Rated cross-section	2.5 mm ²
Contamination degree	3

Connection data

No. of poles	20
Screw head	Slotted
Screw threading	M 2,5
Tightening torque, min.	0.4 Nm
Tightening torque, max.	0.8 Nm

Materials

Material	Copper
Surface	Tin-plated
Surface screw	Galvanized

Further technical data

Mounting type	Screwable
Number of bridged terminals	20

Technical data

Environmental Product Compliance

REACH Conform	No
REACH Reference date	2024-01-23
REACH Candidate Substance Note	No
REACH CAS 1 Substance	LEAD
REACH CAS 1 Percent minimal	0.1 %
REACH CAS 1 Percent maximum	4 %
REACH CAS 1 Number	7439-92-1
RoHS Conform	yes
RoHS Exception rule	6c
SCIP	7f4b9213-f7f4-4c2f-bf65-cc2e115d3d45

Media



Accessories


Screwdriver

Screwdriver with bare blade, Colour: Black-grey



Article number	Article name	GTIN (EAN)	Packaging unit
<u>1086.0</u>	SDB 0,6x3,5	4044211014797	1 ST

##INVERSE##CONTA-CONNECT



Three-level initiator terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1262.2</u>	IK 2,5 PNP/DC/LED(RD)/24V BG	4044211035655	100 ST