

Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Pitch size: 7.5 mm, Colour: Red

Business data

business data	
Article number	27084.9
Article name	PQI 4/2/PTKS RD
GTIN (EAN)	4044211245832
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	1.9 g
Weight per piece (including packaging)	1.95 g
Unit of weight	G
Customs number	85369010
Country of origin	DE
Prio-Article	27084.9
Product description	Insulated cross-connector
Colour	Red

Data sheet






Technical data	
Dimensions	
Length	4 mm
Width	11.5 mm
Height	21.5 mm
Pitch size	7.5 mm
Ratings	
Max. voltage	800 V
Rated current	32 A
Current load, max.	32 A
Rated cross-section	4 mm²
Contamination degree	3
Connection data	
No. of poles	2
Materials	
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C
Further technical data	
Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	2
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet





Media



Data sheet





Accessories

##INVERSE##CONTA-CONNECT



Transformer terminal, Push-in connection, Mounting type: Custom profile, Rated cross-section: 4 mm², Width: 15 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27081.6	PTKS 4/2 GR	4044211242817	25 ST



Transformerterminal for building odd pole numbers, Push-in connection, Mounting type: Custom profile, Rated cross-section: 4 mm², Width: 8.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27080.6	PTKS 4/1 GR	4044211242800	50 ST

##INVERSE##CONTA-CONNECT



Transformer terminal, Push-in connection, Mounting type: Custom profile, Rated cross-section: 4 mm², Width: 15 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27081.6	PTKS 4/2 GR	4044211242817	25 ST