

Insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Pitch size: 7.5 mm, Colour: Red

Business data

Buomoco uata	
Article number	27085.9
Article name	PQI 4/3/PTKS RD
GTIN (EAN)	4044211245849
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	3.1 g
Weight per piece (including packaging)	3.16 g
Unit of weight	G
Customs number	85369010
Country of origin	DE
Prio-Article	27085.9
Product description	Insulated cross-connector
Colour	Red
	<u> </u>

Data sheet






Technical data		
Dimensions		
Length	4 mm	
Width	19 mm	
Height	21.5 mm	
Pitch size	7.5 mm	
Ratings		
Max. voltage	800 V	
Rated current	32 A	
Current load, max.	32 A	
Rated cross-section	4 mm²	
Contamination degree	3	
Connection data		
No. of poles	3	
Materials		
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-0	
Working temperature, min.	-40 °C	
Working temperature, max.	120 °C	
Further technical data		
Mounting type	Plug in	
Insulation available	✓	
Touch protection is available	✓	
Number of bridged terminals	3	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2023-06-14	
REACH Candidate Substance Note	No	
RoHS Conform	yes	

Data sheet 27085.9 PQI 4/3/PTKS RD



Media



Data sheet





Accessories

##INVERSE##CONTA-CONNECT



Transformer terminal, Push-in connection, Mounting type: Custom profile, Rated cross-section: 4 mm², Width: 15 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27081.6	PTKS 4/2 GR	4044211242817	25 ST



Transformerterminal for building odd pole numbers, Push-in connection, Mounting type: Custom profile, Rated cross-section: 4 mm², Width: 8.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27080.6	PTKS 4/1 GR	4044211242800	50 ST

##INVERSE##CONTA-CONNECT



Transformer terminal, Push-in connection, Mounting type: Custom profile, Rated cross-section: 4 mm², Width: 15 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27081.6	PTKS 4/2 GR	4044211242817	25 ST