Insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 9.6 mm, Colour: Red

Business data

Article number	27123.9
Article name	PQI 1,5/3 RD
GTIN (EAN)	4044211225179
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	0.97 g
Weight per piece (including packaging)	1.02 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	27123.9
Product description	Insulated cross-connector

Data sheet
27123.9 PQI 1,5/3 RD

Technical data

Dimensions

Length	3.2 mm
Width	9.6 mm
Height	14.5 mm
Pitch size	3.5 mm

Ratings

Max. voltage	500 V
Rated current	17.5 A
Current load, max.	17,5 A
Rated cross-section	1.5 mm²
Contamination degree	3

Connection data

No. of poles	3

Materials

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C

Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	3

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2024-01-23
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet

27123.9 PQI 1,5/3 RD

Media

![CONTACLIP logo]

Accessories

##INVERSE##CONTA-CONNECT

Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 1.5 mm², Width: 3.5 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27001.2	PSL 1,5/2A GNYE	4044211223687	50 ST

Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 1.5 mm², Width: 3.5 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27003.2	PSL 1,5/3A GNYE	4044211223724	50 ST

Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 1.5 mm², Width: 3.5 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27005.2	PSL 1,5/4A GNYE	4044211223762	50 ST