



Insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 21.7 mm, Colour: Red

Business data

Duomoco data	
Article number	27153.9
Article name	PQI 6/3 RD
GTIN (EAN)	4044211225353
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	4.4 g
Weight per piece (including packaging)	4.48 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	27153.9
Product description	Insulated cross-connector

Data sheet





Technical data			
Dimensions			
Length	4 mm		
Width	21.7 mm		
Height	22.5 mm		
Pitch size	8.1 mm		
Ratings			
Max. voltage	800 V		
Rated current	41 A		
Current load, max.	41 A		
Rated cross-section	6 mm²		
Contamination degree	3		
Connection data			
No. of poles	3		
Materials			
Insulation housing	Polyamide 6.6		
Flammability class UL 94	V-0		
Working temperature, min.	-40 °C		
Working temperature, max.	120 °C		
Further technical data			
Mounting type	Plug in		
Insulation available	✓		
Touch protection is available	✓		
Number of bridged terminals	3		
Environmental Product Compliance			
REACH Conform	yes		
REACH Reference date	2023-06-14		
REACH Candidate Substance Note	No		
RoHS Conform	yes		

Data sheet 27153.9 PQI 6/3 RD



Media

Data sheet 27153.9 PQI 6/3 RD



Accessories

Data sheet

27153.9 PQI 6/3 RD



##INVERSE##CONTA-CONNECT

Three-level initiator terminal |Multi-wire terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27050.6	PIKD 2,5/1/L/L GR	4044211227302	50 ST

Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27021.2	PSL 6/3A GNYE	4044211223960	50 ST

Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27023.2	PSL 6/4A GNYE	4044211224004	50 ST

Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27019.2	PSL 6/2A GNYE	4044211223922	50 ST

Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5,Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27022.6	PRK 6/4A GR	4044211223991	50

Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5,Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Grey

 Article number	Article name	GTIN (EAN)	Packaging unit
27020.6	PRK 6/3A GR	4044211223953	50