

Data sheet

28685.0 BL-VA KDS-SR 8/16



Sheet metal punch for rectangular openings, Dimensions opening: 103 x 46 mm, Maximum wall thickness: 2.0 mm for stainless steel sheet, Material: steel

Business data

Article number	28685.0
Article name	BL-VA KDS-SR 8/16
GTIN (EAN)	4044211218805
Packaging unit	1
Quantity unit	PC
Included in delivery	Stamp, die, pull axis, lock nut, plastic case
Weight per piece (not including packaging)	4000 g
Weight per piece (including packaging)	4000 g
Unit of weight	G
Customs number	82073010
Country of origin	DE
Product description	Sheet-metal puncher

Technical data

Further technical data

Traction axis	3/4"-UNF / 25,0 x 21,0 x 135 mm
Integrated centrepunch	✓

Dimensions

Lenght of wall cutout	91 mm
Width of wall cutout	46 mm
Maximum material thickness for S 235 sheet metal	2 mm
Maximum material thickness for stainless sheet metal	2 mm

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2024-01-23
REACH Candidate Substance Note	No
RoHS Conform	yes

Media




Accessories

##INVERSE##CONTA-CABLE



Cable entry with foamed-in seal, Mounting type: Screws, Length: 126 mm, Width: 70 mm, IP 66, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28502.4	KDS-SR 8/16 BK	4044211210786	1 ST



Cable entry set, IP66, Consisting of: 1 x KDS-SR 8/16, 1 x KDS-Inlay 1, 2 x KDS-Inlay 4

Article number	Article name	GTIN (EAN)	Packaging unit
28604.4	KDS-Set 8/16 BK	4044211216207	1 ST



Cable entry with TPE seal, Mounting type: Screws, Length: 126 mm, Width: 64 mm, IP 66, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28882.4	KDSI-SR 8/16 BK	4044211242091	1 ST



Cable entry set, IP66, Consisting of: 1xKDSI-SR 8/16, 2xKDS-Inlay 4

Article number	Article name	GTIN (EAN)	Packaging unit
28892.4	KDSI-SET 8/16 BK	4044211242176	1 ST