



Sheet metal puncher for rectangular openings, Dimensions opening: $46 \times 24 \text{ mm}$, Maximum wall thickness: 2.0 mm for stainless steel sheet, Material: steel

Business data

business uata	
Article number	<u>28734.0</u>
Article name	BL KDS-FB1
GTIN (EAN)	4044211221805
Packaging unit	1
Quantity unit	PC
Included in delivery	Stamp, die, pull axis, lock nut, plastic case
Weight per piece (not including packaging)	2300 g
Weight per piece (including packaging)	2300 g
Unit of weight	G
Customs number	82073010
Country of origin	DE
Product description	Sheet-metal puncher



Technical data	
Further technical data	
Traction axis	3/4"-UNF / 25,0 x 21,0 x 135 mm
Integrated centrepunch	✓
Dimensions	
Lenght of wall cutout	46 mm
Width of wall cutout	24 mm
Maximum material thickness for S 235 sheet metal	2 mm
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2024-01-23
REACH Candidate Substance Note	No
RoHS Conform	yes



Media





Accessories

##INVERSE##CONTA-CABLE



Cable entry with injected seal, Mounting type: Screws, Length: 73 mm, Width: 39 mm, IP 66, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28700.4	KDS-SR-FB1/A BK	4044211225476	10 ST